Allied Telesis 10/100TX x 48 ports Fast Ethernet Layer 3 Switch Hallittu L3 1U



Tuotemerkki: Allied Telesis **Tuotekoodi**: AT-8648T/2SP-50

Tuotteen nimi: 10/100TX x 48 ports Fast Ethernet Layer

3 Switch

Allied Telesis 10/100TX x 48 ports Fast Ethernet Layer 3 Switch. Kytkin tyyppi: Hallittu, Kytkinkerros: L3. Basic kytkentä RJ-45 Ethernet-porttien määrä: 48. MAC-osoitetaulukko: 8000 entries. Verkkostandardit: IEEE 802.1D, IEEE 802.1p, IEEE 802.1Q, IEEE 802.1s, IEEE 802.1w, IEEE 802.1x, IEEE 802.2, IEEE.... Kotelo: 1U

Management features		Performance	
Switch type *	Managed	Flash memory	8 MB
Switch layer	L3	Power	
Ports & interfaces		Power consumption (typical)	65 W
Basic switching RJ-45 Ethernet ports quantity *	48	Power over Ethernet (PoE)	
Combo SFP ports quantity	2	Power over Ethernet (PoE) *	×
SFP/SFP+ slots quantity	2	Other features	
Network		Dimensions (WxDxH)	438 x 261.6 x 44 mm
Networking standards *	IEEE 802.1D, IEEE 802.1p, IEEE 802.1Q, IEEE 802.1s, IEEE 802.1w, IEEE 802.1x, IEEE 802.2, IEEE 802.3ab, IEEE 802.3ac, IEEE 802.3u,	E 802.1w, Power requirements IEEE Networking features	Wired AC 120/230 V (50/60 Hz) Ethernet, Fast Ethernet
	IEEE 802.3x, IEEE 802.3z	Operational conditions	
IP routing	1	Operating temperature (T-T)	0 - 40 °C
Data transmission		Storage temperature (T-T)	-25 - 70 °C
MAC address table *	8000 entries	Operating relative humidity (H-H)	5 - 80%
Maximum data transfer rate	0.1 Gbit/s	Storage relative humidity (H-H)	5 - 95%
Protocols		Weight & dimensions	
Management protocols	SNMP 2, RMON 1, RMON 2, RMON 3, RMON 9, Telnet, SNMP 3, HTTP RIP1, RIP2, IGMPv2, VRRP, OSPFv2	Weight	3.6 kg
Supported network protocols		Certificates	
Design	,,,	Certification	Safety UL 1950 (UL/cUL), EN60950 (TUV) EMI FCC Class A, EN55022 Class A,VCCI Class A, C-TICK, EN61000-3-2, EN61000-3-3
Stackable *	✓		
Form factor	10		Immunity EN55024
Performance			
Built-in processor Processor model Processor frequency Internal memory	PowerPC 200 MHz 32 MB		
-			

