Allied Telesis GS950/28PS Hallittu Gigabit Ethernet (10/100/1000) Power over Ethernet -tuki Harmaa



Tuotemerkki: Allied Telesis **Tuotekoodi**: AT-GS950/28PS-50

Tuotteen nimi: GS950/28PS

Allied Telesis GS950/28PS. Kytkin tyyppi: Hallittu. Peruskytkentä RJ-45 Ethernet-porttien tyyppi: Gigabit Ethernet (10/100/1000), Basic kytkentä RJ-45 Ethernet-porttien määrä: 24. MAC-osoitetaulukko: 8000 entries, Kytkentäkapasiteetti: 56 Gbit/s. Verkkostandardit: IEEE 802.1D, IEEE 802.1Q, IEEE 802.1p, IEEE 802.1s, IEEE 802.1w, IEEE 802.1x, IEEE 802.3, IEEE.... Power over Ethernet -tuki. Telineasennus

Management features		Security	
Switch type *	Managed	SSH/SSL support	✓
Quality of Service (QoS) support	✓	Multicast features	
Web-based management	✓	Multicast support	✓
System event log	✓	Protocols	
MIB support	✓	Supported network protocols	НТТР
Ports & interfaces			11111
Basic switching RJ-45 Ethernet ports quantity *	24	Design Rack mounting *	✓
Basic switching RJ-45 Ethernet ports	Gigabit Ethernet (10/100/1000)	Product colour	Grey
type *	digabit Ethernet (10/100/1000)	Reset button	✓
SFP module slots quantity	4	Performance	
Fiber optic connector	FX, SX	Memory type	DRAM
Network		Internal memory	64 MB
Networking standards *	IEEE 802.1D, IEEE 802.1Q, IEEE 802.1p, IEEE 802.1s, IEEE 802.1w, IEEE 802.1x, IEEE 802.3, IEEE 802.3ab, IEEE 802.3ad, IEEE 802.3af, IEEE 802.3at, IEEE 802.3az, IEEE 802.3i, IEEE 802.3u, IEEE 802.3u, IEEE	Flash memory	16 MB
		Firmware upgradeable	✓
		Power	
		AC input voltage	100 - 240 V
10G support *	802.3x, IEEE 802.3z	AC input frequency	50 - 60 Hz
Copper ethernet cabling technology		Power consumption (max)	28.6 W
Port mirroring	✓	Power plug type	Type C
IP routing	✓	Power over Ethernet (PoE)	
Flow control support	✓	Power over Ethernet (PoE) *	✓
Link aggregation	✓	Power over Ethernet (PoE) ports	24
Broadcast storm control	✓	quantity Power over Ethernet plus (PoE+)	
Rate limiting	✓	ports quantity	24
Spanning tree protocol	✓	Power over Ethernet (PoE) power per port	30 W
Head-of-line (HOL) blocking	✓	Total Power over Ethernet (PoE)	105.11/
VLAN support	✓	budget	185 W
Virtual LAN features	Private VLAN, Tagged VLAN, Protocol-based VLAN, Port-based VLAN	Operational conditions	
		Operating temperature (T-T)	0 - 45 °C
Number of VLANs	256	Storage temperature (T-T)	-25 - 70 °C
Optical fiber		Operating relative humidity (H-H)	5 - 90%
Fiber ethernet cabling technology	100BASE-FX, 1000BASE-SX,	Storage relative humidity (H-H) Heat dissipation	5 - 95% 97.59 BTU/h
riber ethernet cability technology	1000BASE-LX		37.33 510/11
Data transmission		Weight & dimensions	450 mm
Switching capacity *	56 Gbit/s	Width Depth	450 mm 250 mm
Throughput	41.65 Mpps	Height	44 mm
MAC address table *	8000 entries	Weight	3.6 kg
Number of queues Number of static routes	4 256		-
ואמוווטכו טו אנמנונ וטענפא	230		

Data transmission		Packaging content	
Jumbo frames support	✓	Cables included	AC
Jumbo frames	10000	Quick start guide	✓
Packet forwarding rate (1 Gbps)	1488000 pps	Manual	✓
Packet forwarding rate (100 Mbps) Packet forwarding rate (10 Mbps)	148800 pps 14880 pps 1 MB	Packaging data	
Packet buffer memory		Mounting brackets included	✓
Security		Rubber feet	✓
DHCP features	DHCP client	Resource CD	✓
Access Control List (ACL)	✓	Certificates	
Access Control List (ACL) rules	240	Certification	IEC 68-2-36 IEC 68-2-29 IEC 68-2-32 UL94V-0 RoHS WEEE UL60950-1 2nd edition (UL) FCC/EN55022/CISPR 22 Class A VCCI Class A C-Tick EN60950 (TUV) EN55024 CE Mark CSA / CUL
IGMP snooping	✓		
Security algorithms	SNMP, SSL/TLS		
MAC address filtering	✓		





767035208725

0767035208725

Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.