Allied Telesis GS980MX Hallittu L3 Gigabit Ethernet (10/100/1000) 1U Harmaa



Tuotekoodi: AT-GS980MX/28-50



Tuotteen nimi : GS980MX

Allied Telesis GS980MX. Kytkin tyyppi: Hallittu, Kytkinkerros: L3. Peruskytkentä RJ-45 Ethernet-porttien tyyppi: Gigabit Ethernet (10/100/1000), Basic kytkentä RJ-45 Ethernet-porttien määrä: 24, Asennettujen SFP+ moduulien määrä: 4. Täysin kaksipuolinen. MAC-osoitetaulukko: 16000 entries, Kytkentäkapasiteetti: 128 Gbit/s. Verkkostandardit: IEEE 802.2, IEEE 802.2x, IEEE 802.3, IEEE 802.3ab, IEEE 802.3ae, IEEE 802.3u, IEEE 802.3x, IEEE.... Telineasennus, Kotelo: 1U

Management features		Security	
Switch type *	Managed	BPDU filtering/protection	1
Switch layer	L3	Authentication	 MAC-based authentication
Quality of Service (QoS) support	 Image: A second s	Multicast features	
Web-based management	1		
Traffic classification	✓	Multicast support	v
ARP inspection	✓	Protocols	
Configuring Location Settings (CLI)	✓	Management protocols	SNMP
Ports & interfaces		Design	
Basic switching RJ-45 Ethernet ports quantity *	24	Rack mounting * Stackable *	у У
Basic switching RJ-45 Ethernet ports	Gigabit Ethernet (10/100/1000)	Form factor	10
type *		Product colour	Grey
Installed SFP+ modules quantity *	4	Performance	
Network		Memory type	DDR3-SDRAM
Networking standards *	IEEE 802.2, IEEE 802.2x, IEEE 802.3, IEEE 802.3ab, IEEE 802.3ae, IEEE	Internal memory	16384 MB
	802.3u, IEEE 802.3x, IEEE 802.3z	Flash memory	256 MB
10G support *	1	Noise level	42 dB
Port mirroring	1	Power	
Full duplex	 Image: A set of the set of the	Power source *	AC
IP routing	1	Power supply included *	
Policy-based routing	1	Power consumption (max)	39 W
Flow control support	1	Power over Ethernet (PoE)	
Link aggregation	1	Power over Ethernet (PoE) *	×
Broadcast storm control	1	Operational conditions	
VLAN support	1	Operating temperature (T-T)	0 - 50 °C
Virtual LAN features	Port-based VLAN, Private VLAN, Protocol-based VLAN, Voice VLAN	Storage temperature (T-T) Operating relative humidity (H-H)	-25 - 70 °C 5 - 90%
Data transmission		Storage relative humidity (H-H)	5 - 95%
Switching capacity *	128 Gbit/s	Operating altitude	0 - 3000 m
Forwarding rate	95.2 Mpps	Non-operating altitude	0 - 4000 m
MAC address table *	16000 entries	Heat dissipation	133 BTU/h
Latency (10-100 Mbps)	8.29 μs	Weight & dimensions	
Latency (1 Gbps) Latency (10 Gbps)	7.63 μs 1.63 μs	Width	441 mm
Jumbo frames support	·	Depth	323 mm
Security	·	Height	44 mm
DHCP features	DUCD client, DUCDuc speeping	Weight	4.3 kg
Access Control List (ACL)	DHCP client, DHCPv6 snooping	Packaging content	
IGMP snooping	•	Cables included	AC
MAC address filtering	•	Packaging data	
שחר מעמובים ווונכווווץ	•	Package width	563 mm

Security		Packaging data	
SSH/SSL support	1	Package depth	534 mm
Loop protection	1	Package height	128 mm
		Package weight	6.3 kg





767035213712

0767035213712

Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.