Allied Telesis AT-FS980M/28DP-50 Hallittu L3 Fast Ethernet (10/100) Power over Ethernet -tuki Harmaa

Tuotemerkki: Allied Telesis **Tuotekoodi**: 990-006372-50

Tuotteen nimi: AT-FS980M/28DP-50

Allied Telesis AT-FS980M/28DP-50. Kytkin tyyppi: Hallittu, Kytkinkerros: L3. Peruskytkentä RJ-45 Ethernet-porttien tyyppi: Fast Ethernet (10/100), Basic kytkentä RJ-45 Ethernet-porttien määrä: 24. Täysin kaksipuolinen. MAC-osoitetaulukko: 16000 entries, Kytkentäkapasiteetti: 12,8 Gbit/s. Verkkostandardit: IEEE 802.1AX, IEEE 802.1Q, IEEE 802.1ab, IEEE 802.1p, IEEE 802.1v, IEEE 802.1x, IEEE

802.2, IEEE.... Power over Ethernet -tuki. Telineasennus



Management features		Protocols	
Switch type *	Managed	Routing protocols	RIP, RIP-2
Switch layer	L3	Design	
Quality of Service (QoS) support	✓	Rack mounting *	✓
Traffic classification	✓	Stackable *	✓
ARP inspection	✓	Product colour	Grey
Configuring Location Settings (CLI)	✓	LED indicators	✓
Ports & interfaces		Performance	
Basic switching RJ-45 Ethernet ports quantity *	24	Memory type	DDR2-SDRAM
Basic switching RJ-45 Ethernet ports	Fast Ethernet (10/100)	Internal memory	512 MB
type *	, , , , , ,	Flash memory	128 MB
SFP module slots quantity	4	Noise level	49 dB
Network		Export Control Classification Number (ECCN)	5A992C
	IEEE 802.1AX, IEEE 802.1Q, IEEE 802.1ab, IEEE 802.1p, IEEE 802.1v, IEEE 802.1x, IEEE 802.2, IEEE 802.3, IEEE 802.3ab, IEEE 802.3ac, IEEE 802.3af, IEEE 802.3at, IEEE 802.3x, IEEE 802.3z	Power	
Networking standards *		Power supply included *	✓
•		Number of power supply units	2
		AC input voltage	100 - 240 V
10G support *	×	AC input frequency	50 - 60 Hz
Copper ethernet cabling technology	1000BASE-T	Input current	8 A
Port mirroring	✓	Power consumption (max)	520 W
Full duplex	✓	Power over Ethernet (PoE)	
IP routing	✓	Power over Ethernet (PoE) *	✓
Routing entries	16	Power over Ethernet (PoE) ports	24
Flow control support	✓	quantity Tatal Bayer ever Ethernet (BaE)	
Link aggregation	✓	Total Power over Ethernet (PoE) budget	375 W
Spanning tree protocol	✓	Operational conditions	
VLAN support		Operating temperature (T-T)	0 - 50 °C
Virtual LAN features	Private VLAN, Tagged VLAN, Voice VLAN	Storage temperature (T-T)	-20 - 60 °C
Optical fiber		Operating relative humidity (H-H)	5 - 90%
	1000DASE V	Storage relative humidity (H-H)	5 - 95%
Fiber ethernet cabling technology	1000BASE-X	Operating altitude	0 - 3048 m
Data transmission		Heat dissipation	1800 BTU/h
Switching capacity *	12.8 Gbit/s	Weight & dimensions	
Forwarding rate	9.52 Mpps	Width	440 mm
MAC address table *	16000 entries	Depth	425 mm
Latency (1 Gbps) Jumbo frames support	3.24 µs	Height	44 mm
Jumbo frames	10000	Packaging content	
		Cables included	AC

Security		Certificates	
DHCP features Access Control List (ACL) IGMP snooping Security algorithms	DHCP snooping	Certification	FCC B, EN55022 A, CISPR22:2006, VCCI A, C-Tick, EN 55024, UL 60950-1 Ed2, C22.2 NO.60950-1, EN 60950-1 Ed2, IEC60950-1 Ed.2, EN60950-1 Ed2 CE, cULus, TUV ROHS
country angularity		Logistics data	
Loop protection	✓	Harmonized System (HS) code	85176990
BPDU filtering/protection	✓	, , ,	
Authentication	Guest VLAN, MAC-based authentication, Web-based authentication		
Password protection	✓		
Multicast features			
Multicast support	✓		





767035216690

0767035216690

Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.