



## TP-Link Omada EAP610-Outdoor 1800 Mbit/s Valkoinen Power over Ethernet -tuki

**Tuotemerkki :** TP-Link

**Tuoteperhe:** Omada

**Tuotekoodi:** EAP610-OUTDOOR

**Tuotteen nimi :** EAP610-Outdoor

TP-Link Omada EAP610-Outdoor. 2,4 GHz, 5 GHz, Tiedonsiirron enimmäisnopeus: 1800 Mbit/s. Tietoturva-algoritmit: WEP, WPA, WPA2, WPA3. Ethernet LAN -datanopeudet: 10,100,1000 Mbit/s. Power over Ethernet -tuki. Tuotteen väri: Valkoinen



Features		Ports & interfaces	
2.4 GHz *	✓	Ethernet LAN (RJ-45) ports *	1
5 GHz *	✓	<b>Power</b>	
6 GHz *	✗	Power over Ethernet (PoE) *	✓
Maximum data transfer rate *	1800 Mbit/s	<b>Design</b>	
Maximum data transfer rate (2.4 GHz)	574 Mbit/s	Placement *	Pole, Wall
Maximum data transfer rate (5 GHz)	1201 Mbit/s	Product colour *	White
Ethernet LAN data rates	10,100,1000 Mbit/s	International Protection (IP) code	IP67
Frequency band	2.4 - 5 GHz	LED indicators	✓
Networking standards	IEEE 802.11a, IEEE 802.11ac, IEEE 802.11ax, IEEE 802.11b, IEEE 802.11g, IEEE 802.11n	<b>Antenna</b>	
Number of users	250 user(s)	Antenna type *	Internal
Automatic channel selection	✓	Antenna features	Integrated antenna
Automatic channel scanning	✓	Antenna gain level (max)	5 dBi
MIMO	✓	<b>Weight &amp; dimensions</b>	
MIMO type	Multi User MIMO	Width	280.4 mm
Wi-Fi Multimedia (WMM)/(WME)	✓	Depth	106.5 mm
VLAN support	✓	Height	56.9 mm
Rate limiting	✓	<b>Packaging data</b>	
Wireless isolation	✓	Package width	241 mm
Band steering	✓	Package depth	325 mm
Quality of Service (QoS) support	✓	Package height	67 mm
BeamForming	✓	Package weight	1.29 kg
<b>Security</b>		<b>Packaging content</b>	
Security algorithms *	WEP, WPA, WPA2, WPA3	Quantity per pack	1 pc(s)
MAC address filtering	✓	PoE adapter included	✓
		Mounting kit	✓

Security		Operational conditions	
Number of SSID supported	16	Operating relative humidity (H-H)	10 - 90%
Remote Authentication Dial-In User Service (RADIUS)	✓	Operating temperature (T-T)	-30 - 70 °C
<b>Protocols</b>		Storage temperature (T-T)	-40 - 70 °C
Management protocols	SNMP v1/v2c	Storage relative humidity (H-H)	5 - 90%
<b>Management features</b>		Logistics data	
Web-based management	✓	Harmonized System (HS) code	85176990
Syslog	✓		
Management platform	Omada		



6935364010232



6935364010249



0845973073145



845973073145

Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.