

LG 75TR3DJ-B infonäyttö Interaktiivinen litteä paneeli 190,5 cm (75") IPS 330 cd/m² 4K Ultra HD musta Kosketusnäyttö 16/7

Tuotemerkki: LG Tuotekoodi: 75TR3DJ-B

Tuotteen nimi: 75TR3DJ-B

LG 75TR3DJ-B. Tuotteen muotoilu: Interaktiivinen litteä paneeli. Näytön halkaisija: 190,5 cm (75"), Näytön teknologia: IPS, Näytön erottelutarkkuus: 3840 x 2160 pikseliä, Näytön kirkkaus: 330 cd/m², HD-tyyppi: 4K Ultra HD, Kosketusnäyttö. Toiminta-aika (tunteja/päiviä): 16/7. Tuotteen väri: musta



Display		Design	
3 3 71	Direct-LED	Bezel width (side)	1.77 cm
Display diagonal *	190.5 cm (75")	Bezel width (top)	1.77 cm
Display technology * Display resolution * Display brightness *	IPS 3840 x 2160 pixels 330 cd/m ²	Anti-glare screen	✓
		Performance	
HD type *	4K Ultra HD	Picture-in-Picture	1
Touchscreen *	✓	Operating hours (hours/days)	16/7
Multi-touch	✓	Open Pluggable Specification (OPS)	✓
Response time	8 ms	Power	
Contrast ratio (typical)	1200:1	Power consumption (typical) *	175 W
Viewing angle, horizontal	178°	Energy efficiency class (SDR)	Α
Viewing angle, vertical	178°	AC input voltage	100 - 240 V
Panel life	30000 h	AC input frequency	50 - 60 Hz
Touch response time	60 ms	Computer system	
Ports & interfaces		Computer system *	×
HDMI ports quantity *	4	Windows operating systems	Windows 7, Windows 8, Windows XP
HDMI input ports quantity	3	supported	
HDMI output ports quantity	1	Mac operating systems supported	MacOS
USB port *	✓	Weight & dimensions	
USB ports quantity USB version	6 2.0/3.2 Gen 1 (3.1 Gen 1)	Display width	1709 mm
Audio (L/R) in	2.0/3.2 Gen 1 (3.1 Gen 1) 1	Display depth	86 mm
Audio (L/R) iii Audio (L/R) out	1	Display height	1020 mm
RS-232 interface	· /	Display weight	53 kg
RS-232C	•	Packaging data	
	•	Package width	1950 mm
Audio		Package depth	285 mm
Built-in speaker(s) *	/	Package height	1266 mm
Number of built-in speakers	2	Package weight	85 kg
RMS rated power	24 W	Packaging content	
Design		Remote control included	1
Product design *	Interactive flat panel	Cables included	AC, HDMI, USB
Placement supported * Product colour *	Indoor Black	Operational conditions	
		Operating temperature (T-T)	0 - 40 °C

Design **Operational conditions** VESA mounting *

Panel mounting interface 800 x 400 mm Bezel width (bottom) 4.57 cm

Operating relative humidity (H-H) 10 - 80%





195174011065

0195174011065

Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.