

iiyama ProLite T2754MSC-B1AG tietokoneen litteä näyttö 68,6 cm (27") 1920 x 1080 pikseliä Full HD LED Kosketusnäyttö Monikäyttäjä musta



Tuotemerkki : iiyama

Tuoteperhe: ProLite

Tuotekoodi: T2754MSC-B1AG

Tuotteen nimi : T2754MSC-B1AG

iiyama ProLite T2754MSC-B1AG. Näytön halkaisija: 68,6 cm (27"), Näytön eroteltutarkkuus: 1920 x 1080 pikseliä, HD-tyyppi: Full HD, Näytön teknologia: LED, Vasteaika (tyypillinen): 4 ms, Vakiokuvausuhde: 16:9, Katselukulma, vaakasuora: 178°, Katselukulma, pystysuora: 178°. Sisäiset kaiuttimet. Sisäänrakennettu USB-keskus, USB-keskuksen versio: 3.2 Gen 1 (3.1 Gen 1). VESA-kiinnitys, Korkeudensäätö. Tuotteen väri: musta

Display

| | |
|------------------------------------|-----------------------------|
| Display diagonal * | 68.6 cm (27") |
| Display resolution * | 1920 x 1080 pixels |
| HD type * | Full HD |
| Native aspect ratio * | 16:9 |
| Display technology * | LED |
| Panel type * | IPS |
| LED backlight | ✓ |
| Touchscreen * | ✓ |
| Touchscreen type | Multi-user |
| Touchscreen technology | Projected capacitive system |
| Touch technology | Multi-touch |
| Number of simultaneous touchpoints | 10 |
| Display brightness | 300 cd/m ² |
| Response time * | 4 ms |
| Screen shape * | Flat |
| Contrast ratio (typical) * | 1000:1 |
| Contrast ratio (dynamic) | 80000000:1 |
| Maximum refresh rate * | 60 Hz |
| Viewing angle, horizontal | 178° |
| Viewing angle, vertical | 178° |
| Display number of colours * | 16.78 million colours |
| Pixel pitch | 0.311 x 0.311 mm |
| Digital horizontal frequency | 30 - 83 kHz |
| Display diagonal (metric) | 68.6 cm |

Performance

| | |
|-----------------|---|
| NVIDIA G-SYNC * | ✗ |
| AMD FreeSync * | ✗ |

Multimedia

| | |
|-----------------------|-----|
| Number of speakers | 2 |
| RMS rated power | 4 W |
| Built-in speaker(s) * | ✓ |

Ergonomics

| | |
|-----------------------------------|---|
| VESA mounting * | ✓ |
| Panel mounting interface | 100 x 100 mm |
| Wall mountable | ✓ |
| Height adjustment * | ✓ |
| Height adjustment | 29.8 cm |
| Tilt angle range | 5 - 90° |
| On Screen Display (OSD) | ✓ |
| On Screen Display (OSD) languages | German, Dutch, English, Spanish, French, Italian, Japanese, Polish, Portuguese, Russian |
| Number of OSD languages | 10 |

Power

| | |
|---|-------------|
| Energy efficiency class (SDR) * | F |
| Energy consumption (SDR) per 1000 hours * | 26 kWh |
| Power consumption (typical) * | 27 W |
| Power consumption (standby) * | 0.5 W |
| Power consumption (off) | 0.3 W |
| AC input voltage | 100 - 240 V |
| AC input frequency | 50 - 60 Hz |
| European Product Registry for Energy Labelling (EPREL) code | 519606 |

Operational conditions

| | |
|-----------------------------------|-------------|
| Operating temperature (T-T) | 5 - 35 °C |
| Storage temperature (T-T) | -20 - 60 °C |
| Operating relative humidity (H-H) | 10 - 85% |
| Storage relative humidity (H-H) | 5 - 90% |

Weight & dimensions

| | |
|---------------------|----------|
| Width (with stand) | 618 mm |
| Depth (with stand) | 121 mm |
| Height (with stand) | 418.5 mm |
| Weight (with stand) | 6.6 kg |

| | | | |
|--------------------------------------|-----------------------|-----------------------------------|-----------------------|
| Multimedia | | Packaging data | |
| Built-in microphone | ✘ | Package width | 688 mm |
| Built-in camera * | ✘ | Package depth | 204 mm |
| Design | | Package height | 477 mm |
| Product colour * | Black | Package weight | 8.4 kg |
| Ports & interfaces | | Packaging content | |
| Built-in USB hub * | ✔ | Cables included | AC, HDMI, USB |
| USB hub version | 3.2 Gen 1 (3.1 Gen 1) | Sustainability | |
| Number of upstream ports | 1 | Sustainability certificates | ErP |
| USB Type-A downstream ports quantity | 1 | Other features | |
| USB Touch port | ✔ | Display viewable area (HxV) | 597.89 x 336.31 mm |
| VGA (D-Sub) ports quantity | 1 | Compliance certificates | CE, REACH, RoHS, WEEE |
| HDMI * | ✔ | Mean time between failures (MTBF) | 50000 h |
| HDMI ports quantity | 1 | Logistics data | |
| Audio input | 1 | Harmonized System (HS) code | 85285210 |
| HDCP | ✔ | | |



4948570118632

Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.

Publication date: 19-DEC-2024. Prints or copies of Information are only valid on the printed Publication date