

Philips Signage Solutions 65BDL3117P Digitaalinen litteä infotaulu 165,1 cm (65") ADS 750 cd/m² 4K Ultra HD musta 24/7



Tuotemerkki : Philips

Tuoteperhe: Signage Solutions **Tuotekoodi:** 65BDL3117P/00

Tuotteen nimi : 65BDL3117P

Philips Signage Solutions 65BDL3117P. Tuotteen muotoilu: Digitaalinen litteä infotaulu. Näytön halkaisija: 165,1 cm (65"), Näytön teknologia: ADS, Näytön erottelutarkkuus: 3840 x 2160 pikseliä, Näytön kirkkaus: 750 cd/m², HD-tyyppi: 4K Ultra HD. Toiminta-aika (tunteja/päiviä): 24/7. Tuotteen väri: musta

Display		Performance	
Panel type	ADS	On Screen Display (OSD) languages	Arabic, Simplified Chinese, Traditional Chinese, Danish, German, Dutch, English, Spanish, Finnish, French, Italian, Japanese, Norwegian, Polish, Portuguese, Russian, Swedish, Turkish
Display diagonal *	165.1 cm (65")	Ambient light sensor	✓
Display technology *	ADS	Operating hours (hours/days)	24/7
Display resolution *	3840 x 2160 pixels	Mean time between failures (MTBF)	50000 h
Display brightness *	750 cd/m ²	Power	
HD type *	4K Ultra HD	Power consumption (typical) *	155 W
Touchscreen *	✗	Power consumption (standby) *	0.5 W
Native aspect ratio	16:9	Power consumption (max)	330 W
Response time	8 ms	Energy efficiency class (SDR)	G
Contrast ratio (typical)	1200:1	Energy consumption (SDR) per 1000 hours	156 kWh
Contrast ratio (dynamic)	500000:1	AC input voltage	100 - 240 V
Viewing angle, horizontal	178°	AC input frequency	50 - 60 Hz
Viewing angle, vertical	178°	Energy efficiency scale	A to G
Display number of colours	1.07 billion colours	Computer system	
Pixel pitch	0.372 x 0.372 mm	Computer system *	✗
Display diagonal (metric)	164 cm	Built-in processor *	✗
Supported graphics resolutions	640 x 480 (VGA), 720 x 400, 800 x 600 (SVGA), 1024 x 768 (XGA), 1152 x 864 (XGA+), 1152 x 870, 1280 x 1024 (SXGA), 1280 x 720 (HD 720), 1280 x 800 (WXGA), 1440 x 900, 1600 x 1200 (UXGA), 1680 x 1056, 1920 x 1080 (HD 1080)	Video formats supported	H.264, M-JPEG, MPEG1, MPEG2, WMV3
Supported video modes	480p, 576p, 720p, 1080i, 1080p	Audio formats supported	HEAAC / MPEG, AAC, AAC HE, MP3
Native refresh rate	60 Hz	Image formats supported	BMP, JPEG, PNG
Haze rate	25%	Weight & dimensions	
Ports & interfaces		Display width	1462.3 mm
HDMI ports quantity *	4	Display depth	89.9 mm
HDMI version	2.0	Display height	837.3 mm
HDMI input ports quantity	3	Display weight	27.8 kg
HDMI output ports quantity	1	Packaging content	
DVI port *	✓	Remote control included	✓
DVI-I ports quantity	1	Batteries included	✓
DisplayPorts quantity *	2	Cables included	AC, RS-232
DisplayPorts in	1	Operational conditions	
DisplayPorts out	1	Operating temperature (T-T)	0 - 40 °C
DisplayPort version	1.2	Operating relative humidity (H-H)	20 - 80%
USB port *	✓	Storage temperature (T-T)	-20 - 60 °C
USB ports quantity	1	Storage relative humidity (H-H)	5 - 95%
USB version	2.0	Operating altitude	0 - 3000 m
Ethernet LAN *	✓		
Ethernet LAN (RJ-45) ports	1		
Wi-Fi *	✗		

Ports & interfaces		Certificates	
Audio (L/R) in	1	Certification	CB, BSMI, EAC, EMF, VCCI, PSB, EnergyStar 8.0, ETL, EPA
Audio (L/R) out	1		
RS-232C	✓		
Audio		Logistics data	
Built-in speaker(s) *	✓	Harmonized System (HS) code	85285210
Number of built-in speakers	2	Technical details	
RMS rated power	20 W	Energy saving functions	Smart Power
Design		Keyboard control	Hidden / Lockable
Product design *	Digital signage flat panel	Signal loop through	DisplayPort / RS232 / HDMI / IR Loophthrough
Placement supported *	Indoor	Tiled Matrix	Up to 15 x 15
Orientation	Horizontal/Vertical	Sustainability compliance	✓
Product colour *	Black	Compliance certificates	CE, Federal Communications Commission (FCC)
VESA mounting *	✓	Other features	
Panel mounting interface	400 x 400 mm	Quick start guide	✓
Performance		Network controllable	RS232/RJ-45
Purpose *	Retail	Screen saving functions	✓
On Screen Display (OSD)	✓	Accessories included	AC Switch Cover, Philips logo (x1), Power cable (x3), Remote control & AAA batteries, RS232 cable (3 m)(x1), RS232 daisy chain cable (x1), USB Cover (x1), Wire Clamper (x3)
Number of OSD languages	18	Bezel width	1.49 cm



8712581778743



0685417581689



685417581689

Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.