

Epson EB-PU2120W

Tuotemerkki : Epson

Tuotekoodi: V11HA63940

Tuotteen nimi : EB-PU2120W



- Erittäin kevyt ja pienikokoinen: Maailman pienin ja kevyin 20 000 lumenin projektori¹
- Loistava kuvaalaatu: 20 000 lumenia, 4K-skaalaustekniikka, WUXGA-resoluutio
- Helppokäyttöinen: Yksinkertainen asennus, pinoaminen, linssin säätö ja käyttö
- Luotettava: Parannettu pölynkestävyys. IP5x-sertifioitu
- Ympäristöhyödyt: Pienempi virrankulutus, vähemmän pakkausjätettä, kevyempi EB-PU2120W

Epson EB-PU2120W. Projektorin kirkkaus: 20000 ANSI lumenia, Projektioteknologia: 3LCD, Projektorin oletusresoluutio: WUXGA (1920x1200). Valonlähteen tyyppi: Laser, Valonlähteen käyttöikä: 20000 h, Valonlähteen käyttöikä (säästötila): 30000 h. Tarkennus: Moottoroitu, Zoomin malli: Auto, Zoomaussuhde: 1.6:1. Videon käsittely: 10 bittiä, Videon väritilat: Elokuvateatteri, Dynaaminen, Luonnollinen, Esitys, DICOM-tilannetila, Multi-projection, BT.709. Sarjaliitännän tyyppi: RS-232C, Palveluportin tyyppi: USB B-tyyppi

Projector		Features	
Screen size compatibility *	1524 - 25400 mm (60 - 1000")	Country of origin	China
Projector brightness *	20000 ANSI lumens	Password protection	✓
Projection technology *	3LCD	Design	
Projector native resolution *	WUXGA (1920x1200)	Market positioning *	Presentation
Contrast ratio (typical) *	2000:1	Product colour *	White
Native aspect ratio *	16:10	Placement	Ceiling, Desktop, Flying frame
Number of colours	1.07 billion colours	Cable lock slot	✓
Projector brightness (economic mode)	14000 ANSI lumens	Cable lock slot type	Kensington
Matrix size	2.62 cm (1.03")	Power	
Heat dissipation	4423 BTU/h	Power source *	AC
Light source		Power consumption (typical) *	1301 W
Light source type *	Laser	Power consumption (standby) *	0.4 W
Service life of light source *	20000 h	Power consumption (economy mode)	899 W
Service life of light source (economic mode)	30000 h	AC input voltage	200-240 V
Lens system		AC input frequency	50 - 60 Hz
Focus *	Motorized	Software	
Zoom type	Auto	Software support	via: AMX, Crestron (Network), Extron
Zoom ratio	1.6:1	Operational conditions	
Throw ratio	0.35 - 7.41:1	Storage temperature (T-T)	-10 - 60 °C
Horizontal lens shift range	-18 - 18%	Operating relative humidity (H-H)	20 - 80%
Vertical lens shift range	-60 - 60%	Storage relative humidity (H-H)	10 - 90%
Lens position memory	10	Weight & dimensions	
Interchangeable lens	✓	Width	586 mm
Video		Depth	492 mm
Analog signal format system *	Not supported	Height	218 mm
Full HD *	✓	Weight *	24.4 kg
3D *	✗	Package width	715 mm
Video processing	10 bit	Package depth	790 mm
Video colour modes	Cinema, Dynamic, Natural, Presentation, DICOM simulation mode, Multi-projection, BT.709	Package height	335 mm
		Package weight	30.9 kg

Ports & interfaces		Packaging content	
HDBaseT port	✓	Remote control included *	✓
Service port type	USB Type-B	Batteries included	✓
USB 2.0 ports quantity	3	Cables included	AC
USB 2.0 Type-A ports quantity	2	Manual	✓
USB 2.0 Type-B ports quantity	1	Warranty card	✓
Headphone outputs	1	WLAN adapter included	✓
Serial interface type *	RS-232C		
VGA (D-Sub) ports quantity *	1		Inhalt DIY-App, EasyMP Multi PC Projection, Epson Projektor Content Manager, Epson Projektor Management, Epson Projektor Professional Tool
HDMI ports quantity *	1	Bundled software	
DVI port *	✓		
Network		Logistics data	
Ethernet LAN *	✓	Quantity per pack	1 pc(s)
Ethernet LAN (RJ-45) ports	1	Products per pallet	4 pc(s)
Ethernet LAN data rates	10,100,1000 Mbit/s	Pallet gross weight	0 g
Storage		Products per pallet (UK)	4 pc(s)
Card reader integrated *	✗	Pallet weight (UK)	0 g
Features		Harmonized System (HS) code	85286200
Noise level (economic mode)	38 dB	Other features	
Noise level *	45 dB	Supported network protocols	HTTPS, IPv6, SNMP, ESC/VP.net, PJLink



8715946703152

Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.

Publication date: 22-DEC-2024. Prints or copies of Information are only valid on the printed Publication date