



EZVIZ C2C IP-turvakamera Sisätila 1920 x 1080 pikseliä Katto/seinä

Tuotemerkki : EZVIZ

Tuotekoodi: CS-C2C-A0-1E2WF

Tuotteen nimi : C2C

EZVIZ C2C. Malli: IP-turvakamera, Tuettu sijoitus: Sisätila, Yhteysteknologia: Langaton. Kiinnitystyyppi: Katto/seinä, Tuotteen väri: Valkoinen. Objektiivin kuvakulma, vaakasuora: 91°, Objektiivin kuvakulma, pystysuora: 50°, Objektiivin kuvakulma, kulmittain: 108°. Anturin tyyppi: CMOS, Optisen sensorin koko: 25,4 / 3 mm (1 / 3"). Kiinteä polttoväli: 2,8 mm

Performance		Network	
Type *	IP security camera	Bluetooth *	✗
Placement supported *	Indoor	Storage	
Connectivity technology *	Wireless	Built-in HDD *	✗
Day/night mode	✓	Card reader integrated	✓
Infrared (IR) cut-off filter	✓	Compatible memory cards	MicroSD (TransFlash)
Certification	FCC/UL/CE/RoHS/WEEE/REACH	Maximum memory card size	256 GB
Design		Security	
Mounting type *	Ceiling/wall	Password protection	✓
Product colour *	White	Video motion detection	✓
Camera		Security algorithms	64-bit WEP, 128-bit WEP, WPA, WPA-PSK, WPA2, WPA2-PSK
Minimum illumination	0 lx	Anti-flicker	✓
Lens viewing angle, horizontal	91°	Heartbeat	✓
Lens viewing angle, vertical	50°	Mirror	✓
Lens viewing angle, diagonal	108°	Digital watermark	✓
Image sensor		Management features	
Number of sensors	1	Web-based management	✓
Optical sensor size	25.4 / 3 mm (1 / 3")	Power	
Sensor type *	CMOS	Power source type *	DC
Lens system		Power consumption (max)	4 W
Number of lenses *	1	DC output voltage	5
Fixed focal length	2.8 mm	DC output current	1 A
Night vision		Operational conditions	
Night vision *	✓	Operating temperature (T-T)	-10 - 45 °C
Night vision distance	10 m	Operating relative humidity (H-H)	0 - 95%
Video		Weight & dimensions	
Maximum resolution *	1920 x 1080 pixels	Width	38 mm
Video compression formats	H.264, H.265	Depth	58 mm
Supported video modes	1080p	Height	110 mm
Frame rate	25 fps	Weight	100 g
Video streaming	✓	Packaging data	
Noise reduction	✓	Package width	149 mm
Noise reduction technology	3D noise reduction	Package depth	91.5 mm
Bit rate	1 Mbps	Package height	87.5 mm
Audio		Package weight	292 g
Audio system	2-way	Packaging content	
Network		Number of cameras *	1
Ethernet LAN *	✗	Cables included	USB
Networking standards	IEEE 802.11b, IEEE 802.11g, IEEE 802.11n	Mounting kit	✓
Wi-Fi *	✓	Screws included	✓

Network

Wi-Fi data rate (max) 72 Mbit/s

Packaging contentManual 

Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.

Publication date: 19-DEC-2024. Prints or copies of Information are only valid on the printed Publication date