Lexmark CS730de Väri 1200 x 1200 DPI A4

Tuotemerkki : Lexmark

Tuotekoodi: 47C9041

Tuotteen nimi : CS730de

Lexmark CS730de. Tulostustekniikka: Laser, Väri. Suurin toimintajakso: 120000 sivua kuukaudessa. Suurin resoluutio: 1200 x 1200 DPI. Suurin ISO A-luokan paperikoko: A4. Tulostusnopeus (musta, normaalilaatu, A4/US Letter): 40 ppm, Kaksipuolinen tulostus. Tuotteen väri: musta, Valkoinen



Printing		Network	
Print speed (colour, normal quality, A4/US Letter)	40 ppm	Ethernet LAN data rates	10,100,1000 Mbit/s
Colour *	1	Security algorithms	IPSec, MD5, PEAP, SSL/TLS, TLS, TTLS
Print technology *	Laser		DHCP, APIPA (AutoIP), BOOTP,
Duplex printing *	1	Management protocols	RARP, mDNS, IGMP, WINS, DDNS, SNMPv3, SNMPv1, SNMPv2c, Telnet,
Maximum resolution *	1200 x 1200 DPI	Hanagement protocols	NTP, ICMP, HTTP, DNS, ARP, HTTPs
Print speed (black, normal quality, A4/US Letter) *	40 ppm	Performance	(SSL/TLS), Finger
Time to first page (black, normal)	6.4 s	Internal memory *	1024 MB
Time to first page (colour, normal)	7 s	Built-in processor	1024 MB
Features		Sound pressure level (printing)	52 dB
Maximum duty cycle *	120000 pages per month	Sound pressure level (printing)	
Recommended duty cycle	1500 - 15000 pages per month	printing)	53 dB
Printing colours *	Black, Cyan, Magenta, Yellow	Design	
Page description languages *	PCL 5, PCL 6, PDF 1.7, PostScript 3	Market positioning *	Home & office
Printer fonts	PPDS, PostScript	Product colour *	Black, White
Input & output capacity		Built-in display *	×
Total number of input trays *	2	Colour display	1
Total input capacity *	650 sheets	Display diagonal	10.9 cm (4.3")
Total output capacity *	300 sheets	Control type	Touch
Multi-Purpose tray	1	Power	
Multi-Purpose tray input capacity	100 sheets	Power consumption (printing) *	610 W
Maximum input capacity	2850 sheets	Power consumption (ready)	57 W
Maximum output capacity	300 sheets	Energy Star Typical Electricity	0.53 kWh/week
Paper handling		Consumption (TEC)	0.55 KWII/WEEK
Maximum ISO A-series paper size *	A4	System requirements	
Paper tray media types *	Banner, Card stock, Envelopes, Plain paper	Windows operating systems supported	Windows 10, Windows 11, Windows
ISO A-series sizes (A0A9) *			7 x64, Windows 8 x64, Windows 8.1. Windows Vista
ISO A-series sizes (A0A9) * Non-ISO print media sizes	A4, A5, A6 Executive, Folio, Legal, Letter,		7 x64, Windows 8 x64, Windows 8.1, Windows Vista
Non-ISO print media sizes	A4, A5, A6 Executive, Folio, Legal, Letter, Statement, Universal	supported	8.1, Windows Vista Windows Server 2008, Windows
Non-ISO print media sizes JIS B-series sizes (B0B9)	A4, A5, A6 Executive, Folio, Legal, Letter, Statement, Universal B5	supported Linux operating systems supported	 8.1, Windows Vista Windows Server 2008, Windows Server 2008 R2, Windows Server
Non-ISO print media sizes	A4, A5, A6 Executive, Folio, Legal, Letter, Statement, Universal	supported	 8.1, Windows Vista Windows Server 2008, Windows Server 2008 R2, Windows Server
Non-ISO print media sizes JIS B-series sizes (B0B9) Envelopes sizes	A4, A5, A6 Executive, Folio, Legal, Letter, Statement, Universal B5 7 3/4, 9, 10, B5, C5, DL	supported Linux operating systems supported Server operating systems supported	 8.1, Windows Vista Windows Server 2008, Windows Server 2008 R2, Windows Server 2012, Windows Server 2016, Windows Server 2019, Windows
Non-ISO print media sizes JIS B-series sizes (B0B9) Envelopes sizes Paper tray media weight	A4, A5, A6 Executive, Folio, Legal, Letter, Statement, Universal B5 7 3/4, 9, 10, B5, C5, DL	supported Linux operating systems supported Server operating systems supported Operational conditions	 8.1, Windows Vista Windows Server 2008, Windows Server 2008 R2, Windows Server 2012, Windows Server 2016, Windows Server 2019, Windows Server 2022
Non-ISO print media sizes JIS B-series sizes (B0B9) Envelopes sizes Paper tray media weight Ports & interfaces	A4, A5, A6 Executive, Folio, Legal, Letter, Statement, Universal B5 7 3/4, 9, 10, B5, C5, DL 60 - 218 g/m ²	supported Linux operating systems supported Server operating systems supported Operational conditions Operating temperature (T-T)	 8.1, Windows Vista Windows Server 2008, Windows Server 2008 R2, Windows Server 2012, Windows Server 2016, Windows Server 2019, Windows Server 2022 10 - 32 °C
Non-ISO print media sizes JIS B-series sizes (B0B9) Envelopes sizes Paper tray media weight Ports & interfaces Direct printing *	A4, A5, A6 Executive, Folio, Legal, Letter, Statement, Universal B5 7 3/4, 9, 10, B5, C5, DL 60 - 218 g/m ²	supported Linux operating systems supported Server operating systems supported Operational conditions Operating temperature (T-T) Operating relative humidity (H-H)	 8.1, Windows Vista Windows Server 2008, Windows Server 2008 R2, Windows Server 2012, Windows Server 2016, Windows Server 2019, Windows Server 2022
Non-ISO print media sizes JIS B-series sizes (B0B9) Envelopes sizes Paper tray media weight Ports & interfaces Direct printing * USB port *	A4, A5, A6 Executive, Folio, Legal, Letter, Statement, Universal B5 7 3/4, 9, 10, B5, C5, DL 60 - 218 g/m ²	supported Linux operating systems supported Server operating systems supported Operational conditions Operating temperature (T-T) Operating relative humidity (H-H) Weight & dimensions	 8.1, Windows Vista Windows Server 2008, Windows Server 2008 R2, Windows Server 2012, Windows Server 2016, Windows Server 2019, Windows Server 2022 10 - 32 °C 15 - 80%
Non-ISO print media sizes JIS B-series sizes (B0B9) Envelopes sizes Paper tray media weight Ports & interfaces Direct printing * USB port * USB connector	A4, A5, A6 Executive, Folio, Legal, Letter, Statement, Universal B5 7 3/4, 9, 10, B5, C5, DL 60 - 218 g/m ²	supported Linux operating systems supported Server operating systems supported Operational conditions Operating temperature (T-T) Operating relative humidity (H-H)	8.1, Windows Vista ✓ Windows Server 2008, Windows Server 2008 R2, Windows Server 2012, Windows Server 2016, Windows Server 2019, Windows Server 2022 10 - 32 °C

Publication date: 05-JAN-2025. Prints or copies of Information are only valid on the printed Publication date

Network		Weight & dimensions	
Ethernet LAN *	1	Height Weight	413 mm 32 kg
		Packaging data	
	Package width	625 mm	
	Package depth	720 mm	
		Package height	567 mm
		Package weight	38.5 kg

Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.