



Canon i-SENSYS MF553DW Laser A4 1200 x 1200 DPI 43 ppm Wi-Fi

Brand : Canon

Product family: i-SENSYS

Product code: 5160C010

Product name : MF553DW

A4, 43ppm, 1200 x 1200 dpi, Secure PIN print, LCD Colour Touch Screen, USB 2.0, LAN, WLAN, 220-240V Canon i-SENSYS MF553DW. Print technology: Laser, Printing: Mono printing, Maximum resolution: 1200 x 1200 DPI. Copying: Mono copying, Maximum copy resolution: 600 x 600 DPI. Scanning: Colour scanning, Optical scanning resolution: 600 x 600 DPI. Faxing: Mono faxing. Duplex functions: Copy, Print, Scan. Maximum ISO A-series paper size: A4. Wi-Fi. Direct printing. Product colour: Black, White



Printing		Paper handling	
Print technology *	Laser	ISO B-series sizes (B0...B9)	B5
Printing *	Mono printing	Non-ISO print media sizes	Executive, Legal, Letter, Oficio, Statement
Duplex printing *	✓	Envelopes sizes	C5, Com-10, DL, Monarch
Maximum resolution *	1200 x 1200 DPI	Paper tray media weight	60 - 120 g/m ²
Print speed (black, normal quality, A4/US Letter) *	43 ppm	Multi-Purpose Tray media weight	60 - 199 g/m ²
Warm-up time	14 s	Ports & interfaces	
Time to first page (black, normal)	5.7 s	Direct printing *	✓
Secure printing	✓	USB port	✓
Copying		USB 2.0 ports quantity	1
Duplex copying *	✓	Network	
Copying *	Mono copying	Wi-Fi *	✓
Maximum copy resolution *	600 x 600 DPI	Ethernet LAN *	✓
Maximum number of copies	999 copies	Cabling technology	10/100/1000Base-T(X)
Copier resize	25 - 400%	Ethernet LAN data rates	10,100,1000 Mbit/s
N-in-1 copy function	✓	Wi-Fi standards	802.11b, 802.11g, Wi-Fi 4 (802.11n)
N-in-1 copy function (N=)	2, 4	Security algorithms	64-bit WEP, 128-bit WEP, WPA-AES, WPA-PSK, WPA-TKIP, WPA2-AES, WPA2-PSK, WPA2-TKIP
ID-card copy function	✓	Performance	
Scanning		Internal memory *	1024 MB
Duplex scanning *	✓	Built-in processor	✓
Scanning *	Colour scanning	Processor frequency	800 MHz
Optical scanning resolution *	600 x 600 DPI	Sound pressure level (printing)	54 dB
Scanner type *	ADF scanner	Sound pressure level (standby)	24 dB
Scan to	Cloud, E-mail	Design	
Image formats supported	JPEG, TIFF	Product colour *	Black, White
Document formats supported	PDF	Market positioning *	Business
Input colour depth	24 bit	Built-in display *	✓
Output colour depth	24 bit	Display	LCD
Greyscale levels	256	Control type	Touch
Scan drivers	ICA, TWAIN, WIA	Colour display	✓
Fax		Power	
Faxing *	Mono faxing	Power consumption (max)	1430 W
Fax resolution (black)	200 x 100 DPI	Power consumption (printing)	590 W
Modem speed	33.6 Kbit/s	Power consumption (standby)	13.6 W
Fax memory	512 pages	Power consumption (sleep)	0.9 W
Speed dialling	✓	Energy Star Typical Electricity Consumption (TEC)	0.41 kWh/week
Features		AC input voltage	220 - 240 V
Recommended duty cycle	2000 - 75000 pages per month	AC input frequency	50 - 60 Hz
Maximum duty cycle *	150000 pages per month		
Duplex functions *	Copy, Print, Scan		
Printing colours *	Black		
Page description languages	PCL 5e, PCL 6, PostScript 3, UFR II		

Features		System requirements	
Printer fonts	PCL, PostScript	Windows operating systems supported	Windows 10, Windows 11, Windows 8.1
Input & output capacity			Mac OS X 10.11 El Capitan, Mac OS X 10.12 Sierra, Mac OS X 10.13 High Sierra, Mac OS X 10.14 Mojave, Mac OS X 10.15 Catalina, Mac OS X 10.15.3 Catalina, Mac OS X 10.2 Jaguar, Mac OS X 10.3 Panther, Mac OS X 10.4 Tiger, Mac OS X 10.5 Leopard, Mac OS X 10.6 Snow Leopard, Mac OS X 10.7 Lion, Mac OS X 10.8 Mountain Lion, Mac OS X 10.9 Mavericks, Mac OS X 11.0 Big Sur
Total number of input trays *	1	Mac operating systems supported	
Total input capacity *	550 sheets		
Total output capacity *	150 sheets		
Multi-Purpose tray	✓		
Multi-Purpose tray input capacity	100 sheets		
Auto document feeder (ADF)	✓		
Auto document feeder (ADF) input capacity	50 sheets		
Maximum input capacity	2300 sheets	Linux operating systems supported	✓
Paper handling			Windows Server 2008, Windows Server 2008 R2, Windows Server 2012, Windows Server 2012 R2, Windows Server 2016, Windows Server 2019
Maximum ISO A-series paper size *	A4	Server operating systems supported	
Paper tray media types *	Envelopes, Heavy paper, Labels, Plain paper, Postcard, Recycled paper, Thin paper		
ISO A-series sizes (A0...A9) *	A4, A5, A6		
		Operational conditions	
		Operating relative humidity (H-H)	20 - 80%
		Storage temperature (T-T)	10 - 30 °C
		Weight & dimensions	
		Width	494 mm
		Depth	464 mm
		Height	452 mm
		Weight	19.8 kg
		Logistics data	
		Harmonized System (HS) code	84433100



4549292186444

Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.