## ASUS P11C-C/4L Intel C242 LGA 1151 (Socket H4) ATX

Brand: ASUS Product code: 90SB06M0-M0UAY0

Product name: P11C-C/4L

- Powered by the Intel Xeon E platform
- 95W CPU and up to 64GB memory support (4 DIMMs)
- Rack-optimized design maximizes cooling for excellent thermal efficiency
- Flexible expandability with 6 SATA HDDs, 2 PCle Gen3 slots and 1 PCl legacy slot
- Quad Intel I210AT Gigabit Ethernet with teaming support
- Dual M.2 for up to 32Gbps performance and data redundancy
- High-speed mini-SAS HD connections
- TPM-M 2.0 support for enhanced platform integrity
- Complete server management with ASUS Control Center
- Optional ASMB9-iKVM module available for 24/7 remote monitoring and diagnostics

ATX, LGA1151, Intel C242, 4x DDR4 2400/2666, PCI-E x8/x16, 6x SATA3, 4x Intel I210AT, Aspeed AST2500 32MB, USB 3.1, VGA





Processor		Rear panel I/O ports	
Processor manufacturer * Processor socket *	Intel LGA 1151 (Socket H4)	USB 3.2 Gen 2 (3.1 Gen 2) Type-A ports quantity *	2
Compatible processor series *	Intel® Celeron®, Intel® Core™ i3, Intel® Pentium®, Intel® Xeon®	Ethernet LAN (RJ-45) ports * VGA (D-Sub) ports quantity *	1
Memory		Network	
Supported memory types * Number of memory slots * Memory slots type Memory channels ECC compatibility Supported memory clock speeds Maximum internal memory *	DDR4-SDRAM 4 DIMM Dual-channel ECC & Non-ECC 2400,2666 MHz 64 GB	Ethernet LAN LAN controller	✓ Intel® I210-AT
		Features	
		Motherboard chipset * Component for * Motherboard form factor * Motherboard chipset family *	Intel C242 PC ATX Intel
Storage controllers		. ,	incei
RAID levels	0, 1, 5, 10	Expansion slots	1
Graphics		PCI Express x8 slots PCI Express x16 slots	1
Graphics card	AST2500	PCI slots	1
Internal I/O		Number of M.2 (M) slots	2
USB 2.0 connectors * USB 3.2 Gen 1 (3.1 Gen 1) connectors * Number of SATA III connectors *	Gen 1 (3.1 Gen 1) ors *  of SATA III connectors *  of chassis fan connectors  6	Operational conditions	
		Storage temperature (T-T) Operating temperature (T-T) Operating relative humidity (H-H)	10 - 35 °C -40 - 70 °C 20 - 90%
, , ,		Logistics data	
EPS power connector (8-pin)		Harmonized System (HS) code	84733020
TPM connector	<b>/</b>	Packaging data	
		Package weight	1.3 kg

Rear panel I/O ports		Weight & dimensions	
USB 3.2 Gen 1 (3.1 Gen 1) Type-A ports quantity *	2	Width Depth	305 mm 244 mm
		Other features	
		Weight	760 g





4718017055420

0192876055427



192876055427

Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.