


## ASUS P11C-X Intel C242 LGA 1151 (Socket H4) ATX

**Brand :** ASUS

**Product code:** 90SB06Q0-M0UAY0

**Product name :** P11C-X

- Powered by the Intel Xeon E platform
  - 95W CPU and up to 64GB memory support (4 DIMMs)
  - Rack-optimized design maximizes cooling for excellent thermal efficiency
  - Flexible expandability with 6 native SATA 6G ports , two PCIe Gen3 slots and two PCI legacy slots
  - Dual Intel Gigabit Ethernet with teaming support
  - Dual M.2 for independent OS drives with RAID 0/1
  - Supports the latest 10Gb/s USB 3.1 onboard for high transfer speed
  - TPM-M 2.0 support for enhanced platform integrity
  - Complete server management with ASUS Control Center
- ATX, LGA1151, Intel C242, 4x DDR4 2400/2666, PCI-E x8/x16, 6x SATA3, Intel I210AT, i219-LM, Aspeed AST2510 64MB, USB 2.0/3.0/3.1, VGA



<b>Processor</b>		<b>Rear panel I/O ports</b>	
Processor manufacturer *	Intel	USB 2.0 ports quantity *	2
Processor socket *	LGA 1151 (Socket H4)	USB 3.2 Gen 1 (3.1 Gen 1) Type-A ports quantity *	2
Compatible processor series *	Intel® Celeron®, Intel® Core™ i3, Intel® Pentium®, Intel® Xeon®	USB 3.2 Gen 2 (3.1 Gen 2) Type-A ports quantity *	2
<b>Memory</b>		Ethernet LAN (RJ-45) ports *	2
Supported memory types *	DDR4-SDRAM	PS/2 ports quantity	1
Number of memory slots *	4	VGA (D-Sub) ports quantity *	1
Memory slots type	DIMM	<b>Network</b>	
Memory channels	Dual-channel	Ethernet LAN	✓
ECC compatibility	ECC & Non-ECC	LAN controller	Intel® I210-AT, Intel I219LM
Supported memory clock speeds	2400,2666 MHz	<b>Features</b>	
Maximum internal memory *	64 GB	Motherboard chipset *	Intel C242
<b>Graphics</b>		Component for *	PC
Graphics card	AST2510	Motherboard form factor *	ATX
<b>Internal I/O</b>		Motherboard chipset family *	Intel
USB 2.0 connectors *	2	<b>Expansion slots</b>	
USB 3.2 Gen 1 (3.1 Gen 1) connectors *	1	PCI Express x8 slots	1
Number of SATA III connectors *	6	PCI Express x16 slots	1
ATX Power connector (24-pin)	✓	PCI slots	2
Number of chassis fan connectors	6	Number of M.2 (M) slots	2
EPS power connector (8-pin)	✓	<b>Logistics data</b>	
		Harmonized System (HS) code	84733020
		<b>Weight &amp; dimensions</b>	
		Width	305 mm
		Depth	244 mm



4712900951868

Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.

Publication date: 22-DEC-2024. Prints or copies of Information are only valid on the printed Publication date