


Chieftec GPU-1200FC virtalähdeyksikkö 1200 W 20+4 pin ATX ATX musta, Punainen

Tuotemerkki : Chieftec

Tuotekoodi: GPU-1200FC

Tuotteen nimi : GPU-1200FC

Chieftec GPU-1200FC. Kokonaisteho: 1200 W, AC-syöttöjännite: 100 - 240 V, AC-syöttötaajuus: 47 - 63 Hz. Emolevyn virtaliitin: 20+4 pin ATX, Emolevyn virtapiuhan pituus: 60 cm, SATA-virtakaapelin pituus: 150,500 mm. Tarkoitus: PC/palvelin, Virransyöttöyksikön mitat: ATX, 80 PLUS certification: 80 PLUS Gold. Tuotteen väri: musta, Punainen, Jäähdytyksen tyyppi: Aktiivinen, Tuulettimen halkaisija: 14 cm. Tuotteen leveys: 150 mm, Tuotteen syvyys: 160 mm, Tuotteen korkeus: 86 mm



Power		Ports & interfaces	
Total power *	1200 W	PCI Express power cable length	60 cm
AC input voltage *	100 - 240 V	ATX Power connector (24-pin)	✗
AC input frequency	47 - 63 Hz	ATX power connector (20+4 pin)	✓
Input current	14 A	Floppy drive power connector	1
Power factor	0.9	PCI Express connector	✓
Power Factor Correction (PFC) type	Active	Cabling type	Fully-Modular
Combined power (+3.3V)	130 W	Performance	
Combined power (+12V)	1200 W	80 PLUS certification *	80 PLUS Gold
Combined power (+5V)	130 W	Purpose *	PC/Server
Combined power (-12V)	3.6 W	Power supply unit (PSU) form factor *	ATX
Combined power (+5Vsb)	15 W	ATX version	2.53
Max output current (+3.3V)	25 A	Design	
Max output current (+12V)	100 A	Product colour	Black, Red
Max output current (+5V)	25 A	Cooling type	Active
Max output current (-12V)	0.3 A	Fan diameter	14 cm
Max output current (+5Vsb)	3 A	Number of fans	1 fan(s)
Power protection features	Over current, Over power, Over voltage, Overheating, Short circuit, Under voltage	Fan location	Top
Ports & interfaces		On/off switch	✓
Motherboard power connector *	20+4 pin ATX	Weight & dimensions	
Motherboard power cable length	60 cm	Width	150 mm
Number of SATA power connectors	9	Depth	160 mm
SATA power cable length	150,500 mm	Height	86 mm
Peripheral (Molex) power connectors (4-pin) *	3	Weight	3.46 kg
Peripheral (Molex) power cable length	150,700 mm	Packaging data	
EPS power connector (4+4 pin)	✓	Package weight	3.87 kg

Ports & interfaces

PCI Express power connectors (6+2 pin) 8

Technical details

Sustainability compliance ✓
Compliance certificates CE

Logistics data

Harmonized System (HS) code 84733020



0753263077677



753263077677

Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.