

ASUS P11C-M/10G-2T Intel C242 LGA 1151 (pistoke H4) Mini-ITX

Tuotemerkki : ASUS

Tuotekoodi: 90SB07J0-M0UAY0

Tuotteen nimi : P11C-M/10G-2T

ASUS P11C-M/10G-2T. Suoritinvalmistaja: Intel, Prosessorin kanta: LGA 1151 (pistoke H4), Yhteensopivat prosessorit: Intel® Xeon®, Intel Xeon E. Tuetut muistityypit: DDR4-SDRAM, Sisäinen enimmäismuisti: 64 GB, Muistipaikkojen tyyppi: DIMM. Tuetut tallennusasemaliitännät: M.2, SATA III, Tuetut tallennusasematyyppit: HDD & SSD, RAID-tasot: 0, 1, 5, 10. Ethernet-liitännän tyyppi: Gigabit Ethernet, LAN-kontrolleri: Intel® I210-AT. Komponentti (tuotteelle): PC, Emolevyn muototekijä: Mini-ITX, Emolevyn piirisarja: Intel C242



Processor		Internal I/O	
Processor manufacturer *	Intel	TPM connector	✓
Processor socket *	LGA 1151 (Socket H4)	RGB LED pin header	✓
Compatible processor series *	Intel® Xeon®, Intel Xeon E	Rear panel I/O ports	
Intel Xeon series	E-2200, E-2100	USB 3.2 Gen 1 (3.1 Gen 1) Type-A ports quantity *	2
Processor number of cores supported	8	USB 3.2 Gen 2 (3.1 Gen 2) Type-A ports quantity *	2
Memory		Ethernet LAN (RJ-45) ports *	3
Supported memory types *	DDR4-SDRAM	VGA (D-Sub) ports quantity *	1
Number of memory slots *	4	Network	
Memory slots type	DIMM	Ethernet LAN	✓
Memory channels	Dual-channel	Ethernet interface type	Gigabit Ethernet
ECC compatibility	ECC & Non-ECC	LAN controller	Intel® I210-AT
Supported memory clock speeds	2400,2666 MHz	Wi-Fi *	✗
Maximum internal memory *	64 GB	Features	
Supported memory module capacities	4GB, 8GB, 16GB, 32GB	Motherboard chipset *	Intel C242
Storage controllers		Component for *	PC
Supported storage drive types	HDD & SSD	Motherboard form factor *	Mini-ITX
Supported storage drive interfaces *	M.2, SATA III	Expansion slots	
Number of HDDs supported	6	PCI Express x16 (Gen 3.x) slots	7
Number of storage drives supported	7	Number of M.2 (M) slots	2
RAID support	✓	Processor special features	
RAID levels	0, 1, 5, 10	Trusted Platform Module (TPM)	✓
Graphics		Operational conditions	
Parallel processing technology support *	Not supported	Storage temperature (T-T)	-40 - 70 °C
Internal I/O		Operating temperature (T-T)	-10 - 35 °C
USB 2.0 connectors *	1	Operating relative humidity (H-H)	20 - 90%

Internal I/O		Operational conditions	
Number of SATA III connectors *	6	Storage relative humidity (H-H)	20 - 90%
ATX Power connector (24-pin)	✓	Logistics data	
Number of chassis fan connectors	1	Harmonized System (HS) code	84733020
Chassis intrusion connector	✓	Weight & dimensions	
Peripheral (Molex) power connectors (4-pin)	3	Width	170 mm
		Depth	170 mm
		Other features	
		Number of DIMM slots	4
		Number of processors supported	1



4718017284424

Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.

Publication date: 26-DEC-2024. Prints or copies of Information are only valid on the printed Publication date