ZYXEL

Zyxel USG FLEX 50 laitteistopalomuuri 0,35 Gbit/s

Tuotemerkki : Zyxel Tuotekoodi: USGFLEX50-EU0101F

Tuotteen nimi: USG FLEX 50

Zyxel USG FLEX 50. Palomuurin välityskyky: 0,35 Gbit/s, VPN-välityskyky: 0,09 Gbit/s. Lämmön poisohjaus: 40,92 BTU/h, Samanaikaisia käyttäjiä: 15 käyttäjiä (t), Keskimääräinen vikaantumisaika: 655130 h. Tietoturva-algoritmit: 3DES, 256-bit AES, DES, HTTPS, IPSec, MD5, SHA-1, SHA-2. Hallintaprotokolla: SNMP v1, v2c, v3. Yhteysteknologia: Langallinen, Ethernet LAN -datanopeudet: 10,100,1000 Mbit/s, WAN-portti: Ethernet (RJ-45)

Data transmission		Ports & interfaces	
Firewall throughput * VPN throughput Maximum firewall connections	0.35 Gbit/s 0.09 Gbit/s 20000	Number of console ports WAN connection DC-in jack	1 Ethernet (RJ-45) ✓
Performance		Design	
Built-in processor Heat dissipation	X 40.92 BTU/h	Built-in fan	×
Concurrent users Syslog Mean time between failures (MTBF)	15 user(s) ✓ 655130 h	Input current DC input voltage Power consumption (max)	2.0 A 12 V 12 W
Network		Certificates	
Wi-Fi Concurrent SSL/VPN connections (default)	x 5	Certification	FCC Part 15 (Class B), IC, CE EMC (Class B), RCM, BSMI
Concurrent SSL/VPN connections	15	Operational conditions	
(maximum) VPN tunnels quantity Static route	15 10 •	Operating temperature (T-T) Storage temperature (T-T) Operating relative humidity (H-H)	0 - 40 °C -30 - 70 °C 10 - 90%
Security		Storage relative humidity (H-H)	10 - 90%
Security algorithms	3DES, 256-bit AES, DES, HTTPS, IPSec, MD5, SHA-1, SHA-2	Weight & dimensions Width	216 mm
DDoS protection Firewall security	/	Depth Height	143 mm 33 mm
Protocols		Weight	880 g
Management protocols	SNMP v1, v2c, v3	Packaging data	
Management features LED indicators Web-based management	* *	Package width Package height Package depth Package weight	276 mm 185 mm 98 mm 1.41 kg
URL filtering	✓	Packaging content	
Ports & interfaces		Cables included	LAN (RJ-45)
Connectivity technology USB 2.0 ports quantity Ethernet LAN (RJ-45) ports Ethernet LAN data rates	Wired 1 4 10,100,1000 Mbit/s	Other features Firewall throughput VPN throughput	350 Mbit/s 90 Mbit/s



4718937626380

Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.