

## Jabra 4099-410-299 kuulokkeet ja kuulokemikrofoni Langallinen Pääpanta Toimisto/puhelukeskus USB Type-C musta

**Tuotemerkki :** Jabra

**Tuotekoodi:** 4099-410-299

**Tuotteen nimi :** 4099-410-299

- Reaaliaikaiset ohjeet (vaatii Engage+ :n)\*
  - 2:n mikrofonin järjestelmä
  - Mukavuutta koko päiväksi
  - Johdossa oleva puhelunohjausyksikkö
  - Kestävä, 3 vuoden takuu
  - Sisäänrakennettu käytössä-valo
- Jabra Engage 40

[Jabra 4099-410-299 kuulokkeet ja kuulokemikrofoni Langallinen Pääpanta Toimisto/puhelukeskus USB Type-C musta:](#)

Tapaa Jabra Engage 40, uuden sukupolven asiakaspalvelukuuloke. Valta parantaa asiakastytyväisyyttä on nyt sinun käsissäsi. Engage+-ohjelmistomme antaa asiakaspalvelijoidesi käyttöön hyödyllisiä, reaaliaikaisia puhelutietoja, joiden avulla he voivat tehostaa työtään ja parantaa asiakastytyväisyyttä. Innovatiivinen puheen optimointi ja kuulonsuojaus sekä tehokas kahden mikrofonin järjestelmä tuottavat upean äänikokemuksen. Myöskään käyttäjäkokemusta ei ole unohdettu: kuulokkeissa on erittäin kevyt mutta samalla kestävä muotoilu, mukautettava istuvuus sekä mukavat, melua vaimentavat korvapehmusteet. Voit keskittyä siihen, mikä on tärkeintä. Me hoidamme loput.



Performance		Microphone	
Product type *	Headset	Microphone type *	Boom
Wearing style *	Head-band	Microphone frequency	100 - 14000 Hz
Recommended usage *	Office/Call center	Microphone sensitivity	-38 dB
Headset type	Binaural	Number of microphones	2
Product colour *	Black	MEMS (Micro-Electro-Mechanical System) microphone	✓
Volume control	✗	<b>Operational conditions</b>	
Cable length	1.6 m	Operating temperature (T-T)	-10 - 55 °C
Cable colour	Black	Storage temperature (T-T)	-5 - 55 °C
Optimized for	UC	<b>Weight &amp; dimensions</b>	
Music playback	✓	Width	167 mm
HD voice	✓	Depth	54 mm
Housing material	Plastic	Height	167 mm
<b>Ports &amp; interfaces</b>		Weight	63 g
Connectivity technology *	Wired	<b>Packaging data</b>	
USB connectivity	✓	Package width	185 mm
USB connector	USB Type-C	Package depth	50 mm
Frequency response (music mode)	50 - 20000 Hz	Package height	249 mm
Frequency response (talk mode)	100 - 14000 Hz	<b>Packaging content</b>	
<b>Headphones</b>		Warranty card	✓
Maximum input power	30 mW	Safety sheet	✓
Ear coupling *	Supraaural	<b>Other features</b>	
Driver unit	2 cm	Digital Signal Processing (DSP)	✓



5706991026085

Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.

Publication date: 23-DEC-2024. Prints or copies of Information are only valid on the printed Publication date