



## EZVIZ HB8 Pallomainen IP-turvakamera Sisätila ja ulkotila 2560 x 1440 pikseliä Katto

**Tuotemerkki** : EZVIZ

**Tuotekoodi**: CS-HB8-R100-2C4WDL

**Tuotteen nimi** : HB8

EZVIZ HB8. Malli: IP-turvakamera, Tuettu sijoitus: Sisätila ja ulkotila, Yhteysteknologia: Langaton.  
Kiinnitystyyppi: Katto, Tuotteen väri: Valkoinen, Kotelo: Pallomainen. Objektiivin kuvakulma, vaakasuora: 83°, Objektiivin kuvakulma, pystysuora: 44°, Objektiivin kuvakulma, kulmittain: 100°. Anturin tyyppi: CMOS, Optisen sensorin koko: 25,4 / 3 mm (1 / 3"). Linssin halkaisija: 4 mm



| Performance                    |                    | Network                         |   |
|--------------------------------|--------------------|---------------------------------|---|
| Type *                         | IP security camera | Wi-Fi standards                 | 802.11b, 802.11g, Wi-Fi 4 (802.11n)                   |
| Placement supported *          | Indoor & outdoor   | Wi-Fi data rate (max)           | 150 Mbit/s  |
| Connectivity technology *      | Wireless           | Bluetooth *                     | ✗   |
| Auto-tracking                  | ✓                  | Channel bandwidth               | 20 MHz  |
| Day/night mode                 | ✓                  | Works with the Google Assistant | ✓   |
| Infrared (IR) cut-off filter   | ✓                  | Works with Amazon Alexa         | ✓   |
| Built-in light                 | ✓                  | <b>Storage</b>                  |   |
| Operating frequency            | 2400 - 2483.5 MHz  | Built-in HDD *                  | ✗   |
| <b>Design</b>                  |                    | Card reader integrated          | ✗   |
| Form factor *                  | Spherical          | Flash memory                    | 32000 MB  |
| Mounting type *                | Ceiling            | <b>Ports &amp; interfaces</b>   |   |
| Product colour *               | White              | USB port                        | ✓   |
| Weatherproof                   | ✓                  | <b>Security</b>                 |   |
| <b>Camera</b>                  |                    | Built-in siren                  | ✓   |
| Camera pan control             | ✓                  | Password protection             | ✓   |
| Camera tilt control            | ✓                  | Video motion detection          | ✓   |
| Minimum illumination           | 0 lx               | Security algorithms             | 64-bit WEP, 128-bit WEP, WPA, WPA-PSK, WPA2, WPA2-PSK |
| Lens viewing angle, horizontal | 83°                | Anti-flicker                    | ✓   |
| Lens viewing angle, vertical   | 44°                | Heartbeat                       | ✓   |
| Lens viewing angle, diagonal   | 100°               | Digital watermark               | ✓   |
| Tilt angle range               | -65 - 65°          | <b>Management features</b>      |   |
| Pan range                      | 0 - 340°           | Reset button                    | ✓   |
| Adjustment shutter speed       | Auto               |                                 |   |

|                            |                      |                                   |                       |
|----------------------------|----------------------|-----------------------------------|-----------------------|
| <b>Image sensor</b>        |                      | <b>Power</b>                      |                       |
| Number of sensors          | 1                    | Power source type *               | Battery               |
| Optical sensor size        | 25.4 / 3 mm (1 / 3") | Power consumption (max)           | 10 W                  |
| Progressive scan           | ✓                    | Battery technology                | Lithium-Ion (Li-Ion)  |
| Sensor type *              | CMOS                 | Battery capacity                  | 10400 mAh             |
| <b>Lens system</b>         |                      | Rechargeable battery              | ✓                     |
| <b>Night vision</b>        |                      | <b>Operational conditions</b>     |                       |
| Number of lenses *         | 1                    | Operating temperature (T-T)       | -20 - 50 °C           |
| Lens diameter              | 4 mm                 | Operating relative humidity (H-H) | 0 - 95%               |
| Focus adjustment           | 1.6                  | <b>Weight &amp; dimensions</b>    |                       |
| <b>Video</b>               |                      | Width                             | 116 mm                |
| Night vision *             | ✓                    | Depth                             | 183 mm                |
| Night vision distance      | 15 m                 | Height                            | 166 mm                |
| <b>Audio</b>               |                      | Weight                            | 803 g                 |
| Maximum resolution *       | 2560 x 1440 pixels   | <b>Packaging data</b>             |                       |
| Total megapixels *         | 4 MP                 | Package width                     | 216 mm                |
| Video compression formats  | H.264, H.265         | Package depth                     | 145 mm                |
| Frame rate                 | 15 fps               | Package height                    | 203 mm                |
| Noise reduction            | ✓                    | Package weight                    | 1.06 kg               |
| Noise reduction technology | 3D noise reduction   | <b>Sustainability</b>             |                       |
| Bit rate                   | 2 Mbps               | Sustainability compliance         | ✓                     |
| <b>Network</b>             |                      | Compliance certificates           | CE, REACH, RoHS, WEEE |
| Ethernet LAN *             | ✗                    | <b>Packaging content</b>          |                       |
| Wi-Fi *                    | ✓                    | Number of cameras *               | 1                     |
|                            |                      | Cables included                   | USB                   |
|                            |                      | Screws included                   | ✓                     |
|                            |                      | Drilling template included        | ✓                     |
|                            |                      | Manual                            | ✓                     |

Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.

Publication date: 19-DEC-2024. Prints or copies of Information are only valid on the printed Publication date