



HP USB-C 65W Laptop Charger

Charge your World

Charge most USB-C® devices with just one compact charger. The HP 65W USB-C Laptop Charger provides up to 65W of power, enough for almost any USB-C® device.



*Product image may differ from actual product

Charges Big or Small

Now with smart power that adapts to your charging needs, this laptop charger delivers 15W, 27W, 60W, or 65W of power¹. This will be the only charger you'll want in your bag.

A Universal Solution

Enjoy the flexibility to charge most USB-C® devices¹, whether it's your laptop, tablet, or phone.

Travel-Size

This compact, lightweight charger comfortably fits in your bag without weighing it down. The durable cable and built-in cable management keeps you organized when traveling or commuting.

HP USB-C 65W Laptop Charger



Product number	671R3AA
Compatibility	Compatible with most USB-C® devices
UPC number	(ABB) 196548308514; (ABU) 196548308569
Tariff number	8504407007
Connection type	USB Type-C®
Input frequency	47-63 Hz
Input operating current	1.6 A at 90 VAC max
Input efficiency	89% min at 115 VAC/230 VAC at 20V/3.25A
Output power	65 W
Output voltages	5V/9V/12V/15V/20V
Hold-up time	5 ms at 115 VAC input
Output current limit	8 A max
Connector description	USB Type-C®
Cable length	39.37 in (power cord); 70.9 in (USB Type-C® cable); 100 cm (power cord); 180 cm (USB Type-C® cable)
System Requirements, Minimum	USB Type-C® port
Warranty	HP standard one-year limited warranty.
Certifications and compliances	CE Mark; IEC 60950-1; EN 60950-1; UL 60950-1; UL 62368-1; SELV; C-UL-US; DENAN; EN 55022 Class B; FCC Class B; CCC; NOM-1 NYCE; NORDICS; CISPR 22 Class B; MTBF
What's in the box	AC power adapter USB Type-C® cable 1 Power Cord Warranty Card
Country of origin	Made in China
Dimensions (W x D x H)	97 x 53.5 x 21 mm
Weight	210 g
Package dimensions (W x D x H)	97 x 75 x 237 mm
Package weight	500 g
Master carton quantity	12
Master carton dimensions (W x D x H)	596 x 197 x 250 mm
Master carton weight	6.32 kg
Pallet weight	303.36 kg
Operating temperature range	0 to 35°C; 32 to 95°F
Storage temperature range (Celsius)	-20 to 85°C
Storage temperature range (Fahrenheit)	-4 to 185°F
Over-voltage protection	20V; 29V
Operating humidity range	20 to 95% RH (non-condensing)
Non-operating humidity range	10 to 95% RH
Operating altitude (metric)	Up to 5,000 m
Operating altitude (imperial)	Up to 16,400 ft

HP USB-C 65W Laptop Charger

Messaging Footnotes

¹ Compatible with most devices that charge using USB-C®. Non-HP listed compatible products tested internally by HP.

