**D-Link** 

## D-Link DGS-1210-10P Hallittu L2 Gigabit Ethernet (10/100/1000) Power over Ethernet -tuki 1U musta

Tuotemerkki : D-Link

Tuotekoodi: DGS-1210-10P/E

Tuotteen nimi : DGS-1210-10P

D-Link DGS-1210-10P. Kytkin tyyppi: Hallittu, Kytkinkerros: L2. Peruskytkentä RJ-45 Ethernet-porttien tyyppi: Gigabit Ethernet (10/100/1000), Basic kytkentä RJ-45 Ethernet-porttien määrä: 8. Täysin kaksipuolinen. MAC-osoitetaulukko: 8000 entries, Kytkentäkapasiteetti: 20 Gbit/s. Verkkostandardit: IEEE 802.3, IEEE 802.3ab, IEEE 802.3u, IEEE 802.3x. Virtaliitin: DC-tulo jakkiliitin. Power over Ethernet -tuki. Telineasennus, Kotelo: 1U

Management features		Design	
Switch type *	Managed	Stackable *	<ul> <li>Image: A start of the start of</li></ul>
Switch layer	L2	Form factor	10
Quality of Service (QoS) support		Product colour	Black
Web-based management	<ul> <li>Image: A start of the start of</li></ul>	LED indicators	<ul> <li>Image: A start of the start of</li></ul>
Ports & interfaces		Performance	
Basic switching RJ-45 Ethernet ports quantity *	0	Noise level Mean time between failures (MTBF)	0 dB 729258 h
Basic switching RJ-45 Ethernet ports type *	Gigabit Ethernet (10/100/1000)	Power	
Gigabit Ethernet (copper) ports quantity	8	Power consumption (max)	80.6 W
SFP module slots quantity	2	Power over Ethernet (PoE)	
Power connector	DC-in jack	Power over Ethernet (PoE) *	✓
Network		Power over Ethernet (PoE) ports quantity	8
Networking standards *	IEEE 802.3, IEEE 802.3ab, IEEE 802.3u, IEEE 802.3x	Power over Ethernet plus (PoE+) ports quantity	2
10G support *	×	Total Power over Ethernet (PoE)	78 W
Copper ethernet cabling technology		budget	
Cable types supported	Cat5, Cat5e	Operational conditions	
Port mirroring	1	Operating temperature (T-T)	-5 - 50 °C
Full duplex	1	Storage temperature (T-T)	-20 - 70 °C
Flow control support	1	Operating relative humidity (H-H)	0 - 95%
Link aggregation	1	Storage relative humidity (H-H) Heat dissipation	0 - 95% 373.96 BTU/h
Auto MDI/MDI-X	1		575.90 010/11
Data transmission		Weight & dimensions	
Switching capacity *	20 Gbit/s	Width Depth	280 mm 126 mm
Forwarding rate	14.88 Mpps	Height	44 mm
MAC address table *	8000 entries	Weight	950 g
Store-and-forward	1		550 g
Packet buffer memory	0.512 MB	Packaging data	200
Security		Package width Package depth	288 mm 331 mm
Access Control List (ACL)	1	Package height	72 mm
MAC address filtering	✓	Package weight	2.21 kg
Multicast features		Certificates	
Multicast support	1	Certification	EMI: CE Class A, VCCI Class A, FCC
		Certification	
Design		Certification	Class A, BSMI, CCC











Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.

Publication date: 22-DEC-2024. Prints or copies of Information are only valid on the printed Publication date

