

## DELL E Series E2423HN LED display 60.5~cm (23.8") 1920 x 1080 pixels Full HD LCD Black

Brand : DELL Product family: E Series Product code: DELL-E2423HN

**Product name:** E2423HN

- 60.5cm (23.8") Full HD 1920 x 1080 LED VA
- 8ms, 16:9, 250cd/m<sup>2</sup>, 3000:1
- VGA, HDMI

60.5cm (23.8") Full HD 1920 x 1080 LED VA, 16:9, 250cd/m², 16.7M, 8ms, 178°/178°, 3000:1

## DELL E Series E2423HN LED display 60.5 cm (23.8") 1920 x 1080 pixels Full HD LCD Black:

Get outstanding value with this 23.8-inch FHD monitor featuring a wide viewing angle, HDMI and VGA connectivity, and an eco-conscious design.

DELL E Series E2423HN. Display diagonal: 60.5 cm (23.8"), Display resolution: 1920 x 1080 pixels, HD type: Full HD, Display technology: LCD, Response time: 8 ms, Native aspect ratio: 16:9, Viewing angle, horizontal: 178°, Viewing angle, vertical: 178°. VESA mounting. Product colour: Black





Display		Power	
Display diagonal * Display resolution * HD type * Native aspect ratio * Display technology * Panel type * Backlight type Touchscreen * Display brightness (typical) Response time * Screen shape * Contrast ratio (typical) * Contrast ratio (dynamic)	tratio * 1920 x 1080 pixels Full HD  tratio * 16:9 LCD VA  e LED  * trees (typical) 250 cd/m² 8 ms 18  Flat 19 (typical) 3000:1 19 (dynamic) 3000:1 19 (fresh rate * 60 Hz	Energy efficiency class (SDR) * Energy efficiency class (HDR) * Energy consumption (SDR) per 1000 hours * Power consumption (typical) * Power consumption (standby) * Power consumption (max) Power consumption (off) AC input voltage AC input frequency Power supply type Energy efficiency scale European Product Registry for Energy Labelling (EPREL) code	E Not available  16 kWh  14.17 W  0.3 W  25 W  0.3 W  100 - 240 V  50 - 60 Hz Internal A to G
Maximum refresh rate * Viewing angle, horizontal		Operational conditions	
Viewing angle, vertical Display number of colours * Response time (fast) Pixel pitch Pixel density Horizontal scan range	178° 16.7 million colours 5 ms 0.2745 x 0.2745 mm 93 ppi 30 - 83 kHz	Operating temperature (T-T) Storage temperature (T-T) Operating relative humidity (H-H) Storage relative humidity (H-H) Operating altitude Non-operating altitude	0 - 40 °C -20 - 60 °C 10 - 80% 5 - 90% 0 - 5000 m 5000 - 12192 m
Vertical scan range Viewable size, horizontal Viewable size, vertical Display diagonal (metric) High Dynamic Range (HDR) supported Colour gamut standard Colour gamut	50 - 75 Hz 52.7 cm 29.6 cm 60.47 cm  X  NTSC 83%	Weight & dimensions  Width (with stand)  Depth (with stand)  Height (with stand)  Weight (with stand)  Width (without stand)  Depth (without stand)  Height (without stand)	552.6 mm 171 mm 420.4 mm 3.44 kg 552.6 mm 49.7 mm 331.6 mm

Performance		Weight & dimensions	
Flicker-free technology Low Blue Light technology	<b>/</b>	Weight (without stand) Bezel width (side) Bezel width (top)	3.11 kg 1.28 cm 1.28 cm
Multimedia		Bezel width (bottom)	2.23 cm
Built-in speaker(s) *	×	Packaging data	
Built-in camera *	×	Package weight	5.29 kg
Design		Packaging content	<u>-</u>
Market positioning * Product colour * Front bezel colour Detachable stand	Home Black Black	Stand included Cables included Quick start guide	✔ AC, HDMI, VGA ✔
Feet colour	Black	Sustainability	
Ports & interfaces Built-in USB hub *	×	Sustainability certificates Doesn't contain	ENERGY STAR PVC/BFR
VGA (D-Sub) ports quantity	1	Carbon footprint	
HDMI *	- ✓	Total carbon footprint (kg of CO2e)	503
HDMI ports quantity HDMI version	1 1.4	Total carbon emissions, standard deviation (kg of CO2e)	136
Headphone out *	X	Carbon emissions, manufacturing (kg of CO2e)	341
AC (power) in	<b>✓</b>	Carbon emissions, logistics (kg of CO2e)	25
<b>Network</b> Wi-Fi	×	Carbon emissions, energy usage (kg of CO2e)	134
Ergonomics		Carbon emissions, end-of-life (kg of CO2e)	3
VESA mounting * Panel mounting interface	<b>✓</b> 100 x 100 mm	Total carbon emissions, w/o use phase (kg of CO2e) PAIA version	369 1.3.1
Cable lock slot *	✓	Other features	
Height adjustment *	X	Introduction year	2022
Pivot	X	Heavy metals free	Hg (mercury)
Swivelling Tilt adjustment	×	Compliance certificates	RoHS
Tilt angle range	-5 - 21°		
Plug and Play	✓		
LED indicators	<b>✓</b>		



5397184656914

Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.