



## DELL E Series E2723H tietokoneen litteä näyttö 68,6 cm (27") 1920 x 1080 pikseliä Full HD LCD musta

**Tuotemerkki :** DELL

**Tuoteperhe:** E Series

**Tuotekoodi:** DELL-E2723H

**Tuotteen nimi :** E2723H

DELL E Series E2723H. Näytön halkaisija: 68,6 cm (27"), Näytön erottelutarkkuus: 1920 x 1080 pikseliä, HD-tyyppi: Full HD, Näytön teknologia: LCD, Vasteaika (tyypillinen): 8 ms, Vakiokuvausuhde: 16:9, Katselukulma, vaakasuora: 178°, Katselukulma, pystysuora: 178°. VESA-kiinnitys. Tuotteen väri: musta



Display		Ergonomics	
Display diagonal *	68.6 cm (27")	On Screen Display (OSD)	✓
Display resolution *	1920 x 1080 pixels	LED indicators	Power, Stand-by
HD type *	Full HD	<b>Power</b>	
Native aspect ratio *	16:9	Energy efficiency class (SDR) *	D
Display technology *	LCD	Energy efficiency class (HDR) *	Not available
Panel type *	VA	Energy consumption (SDR) per 1000 hours *	17 kWh
Backlight type	LED	Power consumption (typical) *	17 W
Touchscreen *	✗	Power consumption (standby) *	0.3 W
Display brightness (typical)	300 cd/m <sup>2</sup>	Power consumption (max)	30 W
Response time *	8 ms	Power consumption (off)	0.25 W
Anti-glare screen	✓	AC input voltage	100 - 240 V
Screen shape *	Flat	AC input frequency	50 - 60 Hz
Supported graphics resolutions	640 x 480 (VGA), 720 x 400, 800 x 600 (SVGA), 1024 x 768 (XGA), 1152 x 864 (XGA+), 1280 x 1024 (SXGA), 1600 x 900, 1920 x 1080 (HD 1080)	Input current	1.5 A
Contrast ratio (typical) *	3000:1	Power supply type	Internal
Maximum refresh rate *	60 Hz	Energy efficiency scale	A to G
Viewing angle, horizontal	178°	European Product Registry for Energy Labelling (EPREL) code	1140053
Viewing angle, vertical	178°	<b>Operational conditions</b>	
Display number of colours *	16.7 million colours	Operating temperature (T-T)	0 - 40 °C
Response time (fast)	5 ms	Storage temperature (T-T)	-20 - 60 °C
Pixel pitch	0.3114 x 0.3114 mm	Operating relative humidity (H-H)	10 - 80%
Pixel density	81.57 ppi	Storage relative humidity (H-H)	5 - 90%
Horizontal scan range	30 - 85 kHz	Operating altitude	0 - 5000 m
Vertical scan range	48 - 75 Hz	Non-operating altitude	0 - 12192 m
Viewable size, horizontal	59.8 cm	<b>Weight &amp; dimensions</b>	
Viewable size, vertical	33.6 cm	Width (with stand)	623.3 mm
Viewable size diagonal	68.6 cm	Depth (with stand)	188.3 mm

<b>Display</b>		<b>Weight &amp; dimensions</b>	
Display diagonal (metric)	68.6 cm	Height (with stand)	458.9 mm
High Dynamic Range (HDR) supported	✗	Weight (with stand)	4.5 kg
DDC/CI	✓	Width (without stand)	623.3 mm
Surface hardness	3H	Depth (without stand)	50.4 mm
NTSC coverage (typical)	72%	Height (without stand)	370.9 mm
Heat dissipation	102.39 BTU/h	Weight (without stand)	3.78 kg
Heat dissipation (typical)	58.02 BTU/h	Bezel width (side)	1.27 cm
<b>Performance</b>		Bezel width (top)	1.29 cm
NVIDIA G-SYNC *	✗	Bezel width (bottom)	1.57 cm
AMD FreeSync *	✗	<b>Packaging data</b>	
Flicker-free technology	✓	Package weight	6.77 kg
Low Blue Light technology	✓	<b>Packaging content</b>	
<b>Multimedia</b>		Stand included	✓
Built-in speaker(s) *	✗	Cables included	DisplayPort
Built-in camera *	✗	<b>Sustainability</b>	
<b>Design</b>		Sustainability certificates	ENERGY STAR
Market positioning *	Business	Doesn't contain	PVC/BFR
Product colour *	Black	<b>Carbon footprint</b>	
Front bezel colour	Black	Total carbon footprint (kg of CO2e)	476
Detachable stand	✓	Total carbon emissions, standard deviation (kg of CO2e)	126
Feet colour	Black	Carbon emissions, manufacturing (kg of CO2e)	301
<b>Ports &amp; interfaces</b>		Carbon emissions, logistics (kg of CO2e)	33
Built-in USB hub *	✗	Carbon emissions, energy usage (kg of CO2e)	139
VGA (D-Sub) ports quantity	1	Carbon emissions, end-of-life (kg of CO2e)	4
HDMI *	✗	Total carbon emissions, w/o use phase (kg of CO2e)	338
DisplayPorts quantity	1	PAIA version	1.3.1
DisplayPort version	1.2	<b>Other features</b>	
Headphone out *	✗	Heavy metals free	Hg (mercury)
DC-in jack	✓	<b>Brand-specific features</b>	
<b>Network</b>		Dell Display Manager (DDM) compatibility	✓
Wi-Fi	✗		
<b>Ergonomics</b>			
VESA mounting *	✓		
Panel mounting interface	100 x 100 mm		
Cable management	✓		
Cable lock slot *	✓		
Cable lock slot type	Kensington		
Height adjustment *	✗		
Pivot	✗		
Swivelling	✗		
Tilt adjustment	✓		
Tilt angle range	-5 - 21°		



5397184656921

Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.

Publication date: 23-DEC-2024. Prints or copies of Information are only valid on the printed Publication date