

ZYXEL

Zyxel GS1900-8HP v3 PoE Hallittu L2 Gigabit Ethernet (10/100/1000) Power over Ethernet -tuki musta

Tuotemerkki : Zyxel

Tuotekoodi: GS1900-8HP-EU0103F

Tuotteen nimi : GS1900-8HP v3 PoE



Zyxel GS1900-8HP v3 PoE. Kytin tyyppi: Hallittu, Kytinkerros: L2. Peruskytkentä RJ-45 Ethernet-porttien tyyppi: Gigabit Ethernet (10/100/1000), Basic kytkentä RJ-45 Ethernet-porttien määrä: 8. Täysin kaksipuolinen. MAC-osoitetaulukko: 8000 entries, Kytkentäkapasiteetti: 16 Gbit/s. Verkkostandardit: IEEE 802.1Q, IEEE 802.1p, IEEE 802.1x, IEEE 802.3, IEEE 802.3ab, IEEE 802.3ad, IEEE 802.3af, IEEE....
Virtaliitin: DC-tulo jakkiliitin. Power over Ethernet -tuki



Management features		Multicast features	
Switch type *	Managed	Multicast support	✓
Switch layer	L2	Design	
Quality of Service (QoS) support	✓	Product colour	Black
Web-based management	✓	Reset button	✓
Ports & interfaces		Performance	
Basic switching RJ-45 Ethernet ports quantity *	8	Mean time between failures (MTBF)	533086 h
Basic switching RJ-45 Ethernet ports type *	Gigabit Ethernet (10/100/1000)	Power	
Power connector	DC-in jack	Power source *	AC/DC
Network		AC input voltage	100 - 240 V
Networking standards *	IEEE 802.1Q, IEEE 802.1p, IEEE 802.1x, IEEE 802.3, IEEE 802.3ab, IEEE 802.3ad, IEEE 802.3af, IEEE 802.3at, IEEE 802.3az, IEEE 802.3u, IEEE 802.3x	AC input frequency	50 - 60 Hz
Full duplex	✓	Power consumption (typical)	90 W
Flow control support	✓	Power over Ethernet (PoE)	
Broadcast storm control	✓	Power over Ethernet (PoE) *	✓
Rate limiting	✓	Power over Ethernet (PoE) ports quantity	8
Auto MDI/MDI-X	✓	Total Power over Ethernet (PoE) budget	70 W
VLAN support	✓	Operational conditions	
Data transmission		Operating relative humidity (H-H)	10 - 90%
Switching capacity *	16 Gbit/s	Weight & dimensions	
MAC address table *	8000 entries	Width	250 mm
Number of queues	8	Depth	104 mm
Jumbo frames support	✓	Height	27 mm
Jumbo frames	9216	Weight	710 g
		Certificates	
		Certification	CE, FCC, C-Tick, RoHS

Security

DHCP features	DHCP client
IGMP snooping	✓
Security algorithms	802.1x RADIUS
MAC address filtering	✓

Logistics data

Harmonized System (HS) code	85176990
-----------------------------	----------



4718937621279

Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.

Publication date: 23-DEC-2024. Prints or copies of Information are only valid on the printed Publication date