

Delock Mini DisplayPort 1.4 to DisplayPort adapter with latch 8K 60 Hz

Description

This mini DisplayPort adapter by Delock can be used to connect a DisplayPort monitor to graphics cards with mini DisplayPort ports that have special notches in the slot bracket above the ports. The additional latch of the plug of the adapter snaps into the notch and prevents the adapter from being pulled out unintentionally.



Specification

- Connectors:
 - 1 x mini DisplayPort male with latch >
 - 1 x DisplayPort female
- DisplayPort 1.4 specification
- Downwards compatible to DisplayPort 1.3, 1.2 and 1.1
- Pin 20 is connected (supports 3.3 V)
- Cable gauge: 32 AWG
- Cable diameter: ca. 4.8 mm
- Contacts gold-plated
- LS0H (halogen-free)
- Transmission of audio and video signals
- Data transfer rate up to 32.4 Gb/s
- Resolution up to:
 - Display with DSC support: 7680 x 4320 @ 60 Hz
 - Display without DSC support: 7680 x 4320 @ 30 Hz
 - (depending on the system and the connected hardware)
- Supports HDR
- Supports HDCP 1.4 and 2.2
- Up to 1536 kHz audio sampling rate
- Cable length incl. connectors: ca. 15 cm
- Colour: black

System requirements

- A free mini DisplayPort female

Package content

- Adapter mini DisplayPort to DisplayPort

Item no. 65978

EAN: 4043619659784

Country of origin: China

Package: Poly bag



Images



General

Specification:	HDCP 1.4
	HDCP 2.2
	DisplayPort 1.4
	HDR10

Interface

Connector 1:	1 x Mini DisplayPort 20 pin male
Connector 2:	1 x DisplayPort 20 pin female

Technical characteristics

Data transfer rate:	32.4 Gb/s
Maximum screen resolution:	7680 x 4320 @ 60 Hz

Physical characteristics

Cable diameter:	4.8 mm
Cable length incl. connector:	15 cm
Pin finishing:	gold-plated
Conductor gauge:	32 AWG
Colour:	black