StarTech.com 5G2A2CPDB-USB-C-HUB keskitin USB 3.2 Gen 1 (3.1 Gen 1) Type-C 5000 Mbit/s Harmaa

Tuotemerkki : StarTech.com

Tuotekoodi: 5G2A2CPDB-USB-C-HUB

Tuotteen nimi : 5G2A2CPDB-USB-C-HUB

StarTech.com 5G2A2CPDB-USB-C-HUB. Isäntäkoneen käyttöliittymä: USB 3.2 Gen 1 (3.1 Gen 1) Type-C, Liittimiä: USB 3.2 Gen 1 (3.1 Gen 1) Type-A, USB 3.2 Gen 1 (3.1 Gen 1) Type-C. Tiedonsiirtonopeus: 5000 Mbit/s, Tuotteen väri: Harmaa, Kotelon materiaali: Muovi. Virtalähteen tyyppi: USB, Virrankulutus: 15 W, Ulostulojännite: 5 V. Windows-käyttöjärjestelmätuki: Windows 10, Windows 10 Education, Windows 10 Education x64, Windows 10 Enterprise, Windows 10..., Mac-käyttöjärjestelmätuki: Mac OS X 10.11 El Capitan, Mac OS X 10.12 Sierra, Mac OS X 10.13 High Sierra, Mac OS X 10.14..., Muu käyttöjärjestelmätuki: Android. Tuotteen leveys: 75 mm, Tuotteen syvyys: 42 mm, Tuotteen korkeus: 14 mm

Ports & interfaces

Host interface *	USB 3.2 Gen 1 (3.1 Gen 1) Type-C
Hub interfaces *	USB 3.2 Gen 1 (3.1 Gen 1) Type-A, USB 3.2 Gen 1 (3.1 Gen 1) Type-C
USB 3.2 Gen 1 (3.1 Gen 1) Type-A ports quantity	2
USB 3.2 Gen 1 (3.1 Gen 1) Type-C ports quantity	2
Ports quantity *	4

Features

Data transfer rate *	5000 Mbit/s
Product colour	Grey
Housing material	Plastic
USB Power Delivery (USB PD)	✔
USB Power Delivery revision	3.0
USB Power Delivery up to	100 W
Cable length	0.3 m

Network

UASP support	✔

Power

Power supply type	USB
Power consumption (typical)	15 W
Output voltage	5 V
Output current	0.9 A

System requirements

Other operating systems supported	Android

Weight & dimensions

Width	75 mm
Depth	42 mm
Height	14 mm
Weight	41 g

Packaging data

Package width	142 mm
Package depth	175 mm
Package height	30 mm
Package weight	94 g

Operational conditions

Operating temperature (T-T)	0 - 45 °C
Storage temperature (T-T)	-5 - 70 °C
Operating relative humidity (H-H)	5 - 85%

Sustainability

Sustainability compliance	✔

Logistics data

Master (outer) case width	530 mm
Master (outer) case length	330 mm
Master (outer) case height	310 mm
Products per master (outer) case	60 pc(s)

Technical details

Compliance certificates	RoHS

Other features

System requirements		Other features	
Windows operating systems supported	Windows 10, Windows 10 Education, Windows 10 Education x64, Windows 10 Enterprise, Windows 10 Enterprise x64, Windows 10 Home, Windows 10 Home x64, Windows 10 IOT Core, Windows 10 IoT Enterprise, Windows 10 Pro, Windows 10 Pro x64, Windows 10 x64, Windows 11, Windows 11 x64, Windows 7, Windows 7 Enterprise, Windows 7 Enterprise x64, Windows 7 Home Basic, Windows 7 Home Basic x64, Windows 7 Home Premium, Windows 7 Home Premium x64, Windows 7 Professional, Windows 7 Professional x64, Windows 7 Starter, Windows 7 Starter x64, Windows 7 Ultimate, Windows 7 Ultimate x64, Windows 7 x64, Windows 8, Windows 8 Enterprise, Windows 8 Enterprise x64, Windows 8 Pro, Windows 8 Pro x64, Windows 8 x64, Windows 8.1, Windows 8.1 Enterprise, Windows 8.1 Enterprise x64, Windows 8.1 Pro, Windows 8.1 Pro x64, Windows 8.1 x64	Chipset	Fresco - FL7102, Fresco - FL5001
Mac operating systems supported	Mac OS X 10.11 El Capitan, Mac OS X 10.12 Sierra, Mac OS X 10.13 High Sierra, Mac OS X 10.14 Mojave, Mac OS X 10.15 Catalina, Mac OS X 10.15.3 Catalina, Mac OS X 11.0 Big Sur, Mac OS X 12.0 Monterey, Mac OS X 13.0 Ventura		
Linux operating systems supported	✔		

0065030894807

065030894807