Lenovo ThinkSystem ST650 V2 palvelin Torni (4U) Intel® Xeon Silver 4309Y 2,8 GHz 32 GB DDR4-SDRAM 750 W

Tuotemerkki : Lenovo

Tuoteperhe: ThinkSystem

Tuotekoodi: 7Z74A02TEA



Tuotteen nimi : ST650 V2

Lenovo ThinkSystem ST650 V2. Suoritinperhe: Intel® Xeon Silver, Prosessorin taajuus: 2,8 GHz, Prosessorimalli: 4309Y. Sisäinen muisti: 32 GB, Sisäisen muistin tyyppi: DDR4-SDRAM, Muistin sijoittelu (paikat x koko): 1 x 32 GB. Ethernet LAN, Kaapelitekniikka: 10/100/1000Base-T(X). Virtalähde: 750 W, Vikasietoisen virtalähteen tuki (RPS). Alustatyyppi: Torni (4U)

Processor		Design	
Processor manufacturer * Processor family * Processor model * Processor frequency * Processor boost frequency	Intel Intel Xeon Silver 4309Y 2.8 GHz 3.6 GHz	Product colour	Black
		Rack mounting	1
		Performance	
		Performance management	XClarity Enterprise
Processor cache	12 MB	Trusted Platform Module (TPM)	1
Number of processors installed	1	Trusted Platform Module (TPM)	2.0
Memory		version	
Internal memory *	32 GB	Software	
Internal memory type *	DDR4-SDRAM	Operating system installed *	×
Memory clock speed Memory layout (slots x size)	3200 MHz 1 x 32 GB	Compatible operating systems *	Microsoft Windows Server, Red Hat Enterprise Linux, SUSE Linux
			Enterprise Server, VMware ESXi
Storage		Power	
RAID support *	1	Redundant power supply (RPS)	1
RAID levels	0, 1, 5, 6, 10, 50, 60	support *	750 W
Supported RAID controllers	940-8i 4GB	Power supply * Number of redundant power	
Graphics		supplies installed	1
Maximum graphics card memory	16 MB	Operational conditions	
Network		Operating temperature (T-T)	5 - 45 °C
LAN controller	Broadcom 57416	Storage temperature (T-T)	-40 - 60 °C
Ethernet LAN	 Image: A set of the set of the	Operating relative humidity (H-H)	8 - 90%
Cabling technology	10/100/1000Base-T(X)	Storage relative humidity (H-H)	8 - 90%
Ethernet interface type	10 Gigabit Ethernet	Operating altitude	0 - 3050 m
Ports & interfaces		Logistics data	
Ethernet LAN (RJ-45) ports *	3	Harmonized System (HS) code	84714100
USB 2.0 ports quantity	1	Weight & dimensions	
USB 3.2 Gen 1 (3.1 Gen 1) Type-A ports quantity	5	Width	175 mm
VGA (D-Sub) ports quantity	1	Depth	734 mm
Serial ports quantity	1	Height	462 mm
Design			
Chassis type *	Tower (4U)		







Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.