



APC Smart-UPS On-Line, 6kVA/6kW, Rackmount 4U, 230V, 6x C13+4x C19 IEC outlets, Network Card+SmartSlot, Extended runtime, W/ rail kit, Marine



Brand : APC

Product code: SRT6KRMXLIM

Product name : Smart-UPS On-Line, 6kVA/6kW, Rackmount 4U, 230V, 6x C13+4x C19 IEC outlets, Network Card+SmartSlot, Extended runtime, W/ rail kit, Marine

Smart-UPS On-Line, 6kVA/6kW, Rackmount 4U, 230V, 6x C13+4x C19 IEC outlets, Network Card+SmartSlot, Extended runtime, W/ rail kit, Marine


APC Smart-UPS On-Line, 6kVA/6kW, Rackmount 4U, 230V, 6x C13+4x C19 IEC outlets, Network Card+SmartSlot, Extended runtime, W/ rail kit, Marine. UPS topology: Double-conversion (Online), Output power capacity: 6 kVA, Output power: 6000 W. AC outlet types: C13 coupler, C19 coupler, IEC Jumpers, Power plug: Terminal, AC outlets quantity: 13 AC outlet(s). Battery technology: Sealed Lead Acid (VRLA), Battery life (max): 5 year(s), Battery recharge time: 1 h. Form factor: Rackmount, Product colour: Black, Rack capacity: 4U. Width: 432 mm, Depth: 719 mm, Height: 174 mm



Features		Battery	
UPS topology *	Double-conversion (Online)	Number of batteries supported	1
Output power capacity *	6 kVA	Battery life (max)	5 year(s)
Output power *	6000 W	Battery recharge time	1 h
Waveform *	Sine	Hot-swap battery	✓
Input operation voltage (min) *	160 V	Automatic battery test	✓
Input operation voltage (max) *	275 V		
Input frequency *	40 - 70 Hz	Design	
Output operation voltage (min)	220 V	Form factor *	Rackmount
Output operation voltage (max)	240 V	Rack capacity	4U
Output frequency	50/60 Hz	Product colour *	Black
Surge energy rating	480 J	Display type	LCD
Crest factor	3:1	LED indicators	✓
Emergency Power Off (EPO)	✓	International Protection (IP) code	IP20
Output voltage Total Harmonic Distortion (THD)	3%	Certification	CE, EAC, RCM, VDE, REACH
Noise level	55 dB	Operational conditions	
Surge protection	✓	Operating temperature (T-T)	0 - 40 °C
Audible alarm(s)	✓	Storage temperature (T-T)	-15 - 45 °C
Auto-restart	✓	Operating relative humidity (H-H)	0 - 95%
Temperature voltage compensation	✓	Storage relative humidity (H-H)	0 - 95%
		Operating altitude	0 - 3000 m
		Non-operating altitude	0 - 15000 m
Ports & interfaces		Technical details	
AC outlet types	C13 coupler, C19 coupler, IEC Jumpers	Compliance certificates	RoHS
Power plug	Terminal	Weight & dimensions	
AC outlets quantity	13 AC outlet(s)	Width	432 mm
USB port	✓	Depth	719 mm
USB 2.0 ports quantity	1	Height	174 mm
Serial interface	✓	Weight	60 kg
Ethernet LAN (RJ-45) ports	1	Package width	610 mm
Cabling technology	10/100Base-T	Package depth	960 mm
SmartSlot	✓	Package height	370 mm
Battery		Packaging data	
Battery technology	Sealed Lead Acid (VRLA)	Package volume	67000 cm ³
		Logistics data	
		Products per pallet	6 pc(s)
		Harmonized System (HS) code	85078000



0731304320838



731304320838

Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.

Publication date: 05-NOV-2024. Prints or copies of Information are only valid on the printed Publication date