/IOC

AOC V5 CU34V5C/BK LED display 86.4 cm (34") 3440 x 1440 pixels Wide Quad HD Black

Brand : AOC Product family: V5 Product code: CU34V5C/BK

Product name: CU34V5C/BK

Screen size (inch) 34, Panel resolution 3440x1440, Refresh rate 100 Hz, Response time MPRT 1 ms, Panel type VA, USB-C connectivity USB-C 3.2 x 1 (DP alt mode, upstream, power delivery up to 65 W), HDMI HDMI 2.0 x 1, Display Port DisplayPort 1.2 x 1, D-SUB (VGA) 0x, DVI 0x, Sync technology (VRR) Freesync



AOC V5 CU34V5C/BK LED display 86.4 cm (34") 3440 x 1440 pixels Wide Quad HD Black:

34" VA WQHD panel for maximum productivity, with MultiView, USB-C and PD65W

The AOC CU34V5C is equipped with a 34" VA curved panel with Ultrawide QHD 21:9 resolution for an immersive viewing experience in a three-side frameless chassis that you can tilt and height adjust as needed. Ready to boost your productivity with USB-C with Power Delivery up to 65W, 4 USB ports & HDMI, it also offers Picture by Picture MultiView for the most complex multitasking.



Display		Ports & interfaces	
Display diagonal * Display resolution * HD type * Native aspect ratio * Display technology * Panel type * Backlight type	86.4 cm (34") 3440 x 1440 pixels Wide Quad HD 21:9 LED VA W-LED	Headphone outputs Headphone connectivity HDCP HDCP version AC (power) in Mobile High-Definition Link (MHL)	1 3.5 mm ✓ 2.2 ✓
Touchscreen *	×	Ergonomics	
Display brightness (typical) Response time * Anti-glare screen Screen shape * Screen curvature rating Contrast ratio (typical) * Contrast ratio (dynamic) Maximum refresh rate * Viewing angle, horizontal Viewing angle, vertical	300 cd/m² 1 ms ✓ Curved 1500R 3000:1 20000000:1 100 Hz 178° 178°	VESA mounting * Panel mounting interface Wall mountable Cable lock slot * Cable lock slot type Height adjustment * Height adjustment Pivot Swivelling	100 x 100 mm Kensington 13 cm
Display number of colours * Pixel pitch Pixel density	16.7 million colours 0.23175 x 0.23175 mm 109.7 ppi	Tilt adjustment Tilt angle range Picture-in-Picture	3 - 21°✓
Display diagonal (metric) Surface hardness sRGB coverage (typical) NTSC coverage (typical) Adobe RGB coverage DCI-P3 coverage	86.4 cm 6H 116% 101% 100% 93%	On Screen Display (OSD) On Screen Display (OSD) languages Number of OSD languages	Simplified Chinese, Traditional Chinese, Croatian, Czech, German, Dutch, English, Spanish, Finnish, French, Italian, Japanese, Korean, Polish, Portuguese, Russian, Swedish, Turkish, Ukrainian
		LED indicators	√

Performance		Power	
NVIDIA G-SYNC *		Energy efficiency class (SDR) *	G
	X	Energy efficiency class (HDR) *	G
AMD FreeSync * AMD FreeSync type	✓ FreeSync	Energy consumption (SDR) per 1000 hours *	
Fast charging Flicker-free technology	✓	Energy consumption (HDR) per 1000 hours *	35 kWh
Low Blue Light technology	✓	Power consumption (typical) *	60 W
Brand-specific features	False	Power consumption (standby) *	0.5 W
Multimedia		Power consumption (off)	0.3 W
Number of speakers	2	AC input voltage	100 - 240 V
RMS rated power	10 W	AC input frequency	50 - 60 Hz
Built-in speaker(s) *	✓ ·	Power supply type	Internal
Built-in microphone		Energy efficiency scale	A to G
Built-in camera *	×	European Product Registry for Energy Labelling (EPREL) code	1245431
Design	•	Weight & dimensions	
_	Heme	Width (with stand)	808.1 mm
Market positioning * Product colour *	Home Black	Depth (with stand)	250 mm
Frameless design	JIACK ✓	Height (with stand)	527.3 mm
3		Weight (with stand)	9.34 kg
Front bezel colour	Black	Width (without stand)	808.1 mm
Detachable stand	✓	Depth (without stand)	99.9 mm
Feet colour	Black	Height (without stand)	365.3 mm
Ports & interfaces		Packaging data	
Built-in USB hub *	✓	Package width	189 mm
USB hub version	3.2 Gen 1 (3.1 Gen 1)	Package depth	1071 mm
USB upstream port type	USB Type-C	Package height	500 mm
Number of upstream ports	1	Package weight	11.8 kg
Number of USB Type-C upstream ports quantity	1	Package type	Box
USB Type-A downstream ports		USB cable length	1.8 m
quantity	4	Packaging content	
USB Type-C DisplayPort Alternate Mode	✓	Stand included	✓
USB Power Delivery (USB PD)	✓	Cables included	AC
USB Power Delivery up to	65 W	HDMI cable length	1.5 m
DVI port	×	Other features	
HDMI *	✓	Picture-by-Picture (PbP)	✓
HDMI ports quantity	1	Exterior finish type	Matt
HDMI version	2.0	Mean time between failures (MTBF)	50000 h
DisplayPorts quantity	1	Light effects	×
DisplayPort version	1.2		
Headphone out *	✓		



4038986110198

Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.