Canon

Canon PIXMA G3570 Inkjet A4 4800 x 1200 DPI Wi-Fi

Brand : Canon

Product family: PIXMA

Product code: 5805C006

Product name : G3570

A4, 4800 x 1200 dpi, CIS, 1.35" LCD, USB Hi-Speed (Type B), WLAN, 100-240 V, 50-60 Hz Canon PIXMA G3570. Print technology: Inkjet, Printing: Colour printing, Maximum resolution: 4800 x 1200 DPI. Copying: Colour copying. Scanning: Colour scanning, Optical scanning resolution: 600 x 1200 DPI. Duplex functions: Print. Maximum ISO A-series paper size: A4. Wi-Fi. Direct printing. Product colour: Black





Printing		Ports & interfaces	
Duplex printing mode	Manual Inkjet Colour printing	USB connector	USB Type-B
Print technology *		Network	
Printing *		Wi-Fi *	1
Duplex printing *	✓ 	Ethernet LAN *	×
Maximum resolution *4800 x 1200 DPIPrint speed (ISO/IEC 24734) black11 ppmPrint speed (ISO/IEC 24734) colour6 ppmEconomical printing<	11 ppm	Wi-Fi standards	802.11a, 802.11b, 802.11g, Wi-Fi 4 (802.11n), Wi-Fi 5 (802.11ac)
		Security algorithms	WEP, WPA-PSK, WPA2-PSK
		Mobile printing technologies	Apple AirPrint, Mopria Print Service, PIXMA Cloud Link
Copying		Design	
Duplex copying * Copying * Maximum number of copies Copier resize N-in-1 copy function N-in-1 copy function (N=)	× Colour copying 99 copies 25 - 400% ✓ 2, 4	Product colour * Market positioning * Built-in display * Display Display diagonal Colour display	Black Home & office ✓ LCD 3.43 cm (1.35") ×
Scanning		Power	
Scanning * Optical scanning resolution * Scanner type * Scan technology Scan to Input colour depth Output colour depth	600 x 1200 DPI Flatbed scanner CIS Cloud 16 bit 8 bit	Power consumption (copying) Power consumption (standby) Power consumption (off) Energy Star Typical Electricity Consumption (TEC) AC input voltage AC input frequency	16 W 1.2 W 0.1 W 0.15 kWh/week 100 - 240 V 50 - 60 Hz
Input greyscale depth		System requirements	
Output greyscale depth	8 bit	Windows operating systems supported	Windows 10, Windows 11, Windows 8.1

Fax		System requirements	
Faxing * Features Duplex functions *	× Print	Mac operating systems supported	Mac OS X 10.15 Catalina, Mac OS X 10.15.3 Catalina, Mac OS X 10.2 Jaguar, Mac OS X 10.3 Panther, Mac OS X 10.4 Tiger, Mac OS X 10.5 Leopard, Mac OS X 10.6 Snow Leopard, Mac OS X 10.7 Lion, Mac OS X 10.8 Mountain Lion, Mac OS X 10.9 Mavericks, Mac OS X 11.0 Big Sur, Mac OS X 12.0 Monterey
Ink tank system Number of print cartridges * Printing colours *	✓ 4 Black, Cyan, Magenta, Yellow		
Country of origin Replacement cartridges	Vietnam GI-51 PGBK, GI-51 C, GI-51 M, GI-51 Y	Server operating systems supported	Windows Server 2008 R2, Windows Server 2012 R2, Windows Server 2016, Windows Server 2019, Windows Server 2022
Input & output capacity		Mobile operating systems supported	
Total number of input trays *	1	Other operating systems supported	ChromeOS
Total input capacity *	100 sheets	Operational conditions	
Paper handling		Operating relative humidity (H-H)	10 - 90%
Maximum ISO A-series paper size *	A4	Operating temperature (T-T)	5 - 35 °C
Maximum print size	216 x 1200 mm Envelopes, Glossy paper, High resolution paper, Iron-On Transfers, Matte paper, Photo paper, Plain paper, Semi-glossy paper A4, A5, A6	Weight & dimensions	
Paper tray media types * ISO A-series sizes (A0A9) *		Width Depth Height Weight	416 mm 557 mm 268 mm 6 kg
ISO B-series sizes (B0B9) Non-ISO print media sizes	B5 Executive, Legal, Letter	Packaging data	
Envelopes sizes Photo paper sizes Borderless printing media sizes Custom media width	C5, Com-10, DL 10x15,13x18,18x25,20x25 10x15, 13x18, 20x25, A4, Letter 55 - 216 mm	Package width Package depth Package height Package weight	494 mm 499 mm 277 mm 10.1 kg
Custom media length	89 - 1200 mm	Packaging content	
Paper tray media weight Ports & interfaces	64 - 105 g/m²	Cartridge(s) included Included cartridge capacity (black)	✓6000 pages
Direct printing *	1	Included cartridge capacity (CMY)	7700 pages
USB port	1	Included cartridge capacity (economy mode, black)	7600 pages
		Included cartridge capacity (economy mode, CMY)	8100 pages
		Cables included	AC

Bundled software

IJ Printer Assistant Tool



4549292205374

Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.