

Delock CFexpress memory card 64 GB

Description

This flash module by Delock is a memory in CFexpress 1.0 (CFX) type B format. The memory card is particularly suitable for photo and video applications, as the PCI Express standard allows large data to be exchanged very fast. In addition, the PCIe resp. NVMe standard and the low latencies make the card suitable for industrial applications in which removable storage media are required.



Specification

- Connector: 1 x CFexpress 1.0
- Capacity: 64 GB
- Interface: PCIe x2 Rev. 3.0
- Form factor: type B
- Flash type: TLC
- Maximum read speed: 750 MB/s
- Maximum write speed: 230 MB/s
- MTBF: 1.500.000 hours
- Power consumption: max. 1.8 W
- Vibration: 20G
- Shock: 1500G
- Storage temperature: -40 °C ~ 85 °C
- Operating temperature: 0 °C ~ 70 °C
- Supports NVM Express (NVMe)
- Supports TRIM
- Supports S.M.A.R.T.
- Dimensions (LxWxH): ca. 38.5 x 29.6 x 3.8 mm

System requirements

- A free CFexpress slot

Package content

- CFexpress memory card

Item no. 54064

EAN: 4043619540648

Country of origin: Taiwan, Republic of China

Package: Antistatic cover



Images



Interface	
connector:	1 x CFexpress 1.0
Technical characteristics	
Operation temperature:	0° C - 70° C
Storage temperature:	-40 °C ~ 85 °C
Read:	750 MB/s
Maximum power consumption:	1.8 W
MTBF:	1.500.000 hours
Interface:	PCI Express
Shock:	1500 G
Write:	230 MB/s
Capacity:	64 GB
Vibration:	20 G