## be quiet! System Power 10 virtalähdeyksikkö 450 W 20+4 pin ATX **ATX musta**

Tuotemerkki : be quiet!

Tuotekoodi: BN326

Tuotteen nimi : System Power 10

be quiet! System Power 10. Kokonaisteho: 450 W, AC-syöttöjännite: 200 - 240 V, AC-syöttötaajuus: 50 Hz. Emolevyn virtaliitin: 20+4 pin ATX, Emolevyn virtapiuhan pituus: 55 cm, SATA-virtakaapelin pituus: 450,550,570,670,690,790 mm. Tarkoitus: PC, Virransyöttöyksikön mitat: ATX, 80 PLUS certification: 80 PLUS Bronze. Tuotteen väri: musta, Jäähdytyksen tyyppi: Aktiivinen, Tuulettimen halkaisija: 12 cm. Tuotteen leveys: 140 mm, Tuotteen syvyys: 86 mm, Tuotteen korkeus: 150 mm





Power		Performance	
Total power *	450 W	Power supply unit (PSU) form factor	ATX
AC input voltage *	200 - 240 V	*	
AC input frequency	50 Hz	ATX version	2.52
Input current	4 A	EPS version	2.92
Power factor	0.95	Noise level	19.2 dB
Power Factor Correction (PFC) type	Active	Bearing technology	Sleeve
Combined power (+3.3V)	100 W	Mean time between failures (MTBF)	
Combined power (+12V)	450 W	Certification	CB, TÜV, cRUus, cTUVus, RCM (Australia), BSMI, CU (Russia)
Combined power (+5V)	100 W	Country of origin	Germany
Combined power (-12V)	3.6 W	Design	
Combined power (+5Vsb)	15 W	-	Plack
Max output current (+3.3V)	20 A 37.5 A	Product colour	Black Active
Max output current (+12V)		Cooling type	12 cm
Max output current (+5V)	20 A	Fan diameter Number of fans	1 fan(s)
Max output current (-12V) Max output current (+5Vsb)	0.3 A 3 A	Fan speed	0 - 1800 RPM
Hold time	17 ms	1	
Efficiency	88.5%	On/off switch	1
Power Good signal delay range	100 - 150 ms	Operational conditions	
Tower bood signal delay range	Over current, Over power, Over	Operating temperature (T-T)	0 - 40 °C
Power protection features	voltage, Overheating, Short circuit,	Storage temperature (T-T)	-20 - 70 °C
	Under voltage	Operating relative humidity (H-H)	0 - 90%
Ports & interfaces		Storage relative humidity (H-H)	0 - 95%
Motherboard power connector *	20+4 pin ATX	Weight & dimensions	
Motherboard power cable length	55 cm	Width	140 mm
Number of SATA power connectors	5	Depth	86 mm
Number of PATA power connectors	1	Height	150 mm
SATA power cable length	450,550,570,670,690,790 mm	Weight	1.74 kg
Peripheral (Molex) power connectors (4-pin) *	1	Packaging data	
Peripheral (Molex) power cable length	790 mm	Manual	✓ German, English, Spanish, French,
		Manual lan average	
PCI Express power connectors (6+2 pin)	2	Manual languages	Polish, Russian
pin)	Z	Package width	195 mm
	2 65 cm		

- -

Ports & interfaces		Packaging data	
CPU power cable length	60 cm	Package weight	2.1 kg
ATX power connector (20+4 pin)	1	Technical details	
Cabling type	Non-Modular	Sustainability certificates	ENERGY STAR, ErP
Performance		Warranty period	5 year(s)
80 PLUS certification * Purpose *	80 PLUS Bronze PC	Compliance certificates	CCC, CE, Federal Communications Commission (FCC), RoHS, WEEE
		Other features	
		Screws included	1

Noise level (silent mode, <30%)

Noise level (quiet mode, 50%)9.8 dBNoise level (full-load mode, 100%)19.2 dB

8.7 dB



4260052189061

Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.