

D-Link EAGLE PRO AI AX3200 Kaksitaajuus (2,4 GHz/5 GHz) Wi-Fi 6 (802.11ax) Valkoinen 2

Tuotemerkki : D-Link

Tuotekoodi: M32-2

Tuotteen nimi : EAGLE PRO AI AX3200

D-Link EAGLE PRO AI AX3200. Tuotteen väri: Valkoinen, Tuotetyyppi: Verkkojärjestelmä, LED-merkkivalot: Tila, Teho. Wi-Fi-taajuus: Kaksitaajuus (2,4 GHz/5 GHz), Wi-Fi-standardi: Wi-Fi 6 (802.11ax), Wi-Fi-standardit: Wi-Fi 5 (802.11ac), 802.11b, Wi-Fi 6 (802.11ax), 802.11g, Wi-Fi 4 (802.11n). Virtuaaliavustaja: Amazon Alexa & Google Assistant, Palomuurisuojaus: DoS, Tuetut käyttöjärjestelmät: Android, iOS. Virrankulutus: 15,51 W, AC-syöttöjännite: 12 V, Verkkolaitteen tulovirta: 2 A. Vaatimustenmukaisuustodistukset: CE



Design		Ports & interfaces	
Product type	Mesh system	Ethernet LAN (RJ-45) ports *	2
Product colour *	White	Ethernet WAN	✓
LED indicators	Status, Power	DC-in jack	✓
Antennas quantity	4	Power	
Maximum coverage	510 m ²	Power consumption (typical)	15.51 W
Reset button	✓	AC input voltage	12 V
Wireless LAN features		AC adapter input current	2 A
Wi-Fi band *	Dual-band (2.4 GHz / 5 GHz)	AC adapter output voltage	12 V
Top Wi-Fi standard *	Wi-Fi 6 (802.11ax)	Certificates	
Wi-Fi standards	Wi-Fi 5 (802.11ac), 802.11b, Wi-Fi 6 (802.11ax), 802.11g, Wi-Fi 4 (802.11n)	Compliance certificates	CE
WLAN data transfer rate (first band)	800 Mbit/s	Sustainability	
WLAN data transfer rate (second band)	2400 Mbit/s	Sustainability compliance	✓
Networking standards	IEEE 802.11k, IEEE 802.11n, IEEE 802.3ab, IEEE 802.11a, IEEE 802.11ac, IEEE 802.11v, IEEE 802.11ax, IEEE 802.11b, IEEE 802.1p, IEEE 802.3u, IEEE 802.11g, IEEE 802.11h, IEEE 802.1Q	Operational conditions	
Security algorithms	WPA2, WPA3, WPA	Operating temperature (T-T)	0 - 40 °C
Point-to-point protocol over Ethernet (PPPoE)	✓	Storage temperature (T-T)	-20 - 65 °C
Dynamic IP	✓	Operating relative humidity (H-H)	5 - 95%
Static IP	✓	Storage relative humidity (H-H)	10 - 90%
Tagged VLAN	✓	Weight & dimensions	
Features		Width	164.6 mm
Built-in microphone	✓	Depth	71.1 mm
Virtual assistant	Amazon Alexa & Google Assistant	Height	185.7 mm
Quality of Service (QoS) support	✓	Weight	486 g
		Packaging content	
		Number of products included	2 pc(s)
		AC adapter included	✓
		Number of units included	1 pc(s)
		Ethernet cable	✓

Features

Firewall security DoS
Mobile operating systems supported Android, iOS
MU-MIMO technology ✓

Logistics data

Harmonized System (HS) code 85171800



0790069463235



790069463235

Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.