



APC SRTL5KRM2UI UPS-virtalähde Taajuuden kaksoismuunnos (verkossa) 5 kVA 5000 W 10 AC-pistorasia(a)

Tuotemerkki : APC

Tuotekoodi: SRTL5KRM2UI

Tuotteen nimi : SRTL5KRM2UI



APC SRTL5KRM2UI. UPS topologia: Taajuuden kaksoismuunnos (verkossa), Kokonaislähtöteho (VA): 5 kVA, Lähtöteho: 5000 W. Pistorasian tyypit: C13 liitin, C19 liitin, Virtapistoke: Hardwire, Ulostulojen määrä: 10 AC-pistorasia(a). Akkuteknologia: Litiumioni (Li-Ion), Akun jännite: 180 V, Tyypillinen varmuuskopioaika täydellä kuormituksella: 5,25 min. Kotelo: Telineasennettava, Tuotteen väri: musta, Telineen kapasiteetti: 2U. Tuotteen leveys: 432 mm, Tuotteen syvyys: 701 mm, Tuotteen korkeus: 86 mm



Features		Battery	
UPS topology *	Double-conversion (Online)	Battery recharge time	1.5 h
Output power capacity *	5 kVA	Automatic battery test	✓
Output power *	5000 W	Cold start	✓
Waveform *	Sine	Design	
Input operation voltage (min) *	180 V	Form factor *	Rackmount
Input operation voltage (max) *	275 V	Rack capacity	2U
Input frequency *	40/70 Hz	Product colour *	Black
Output operation voltage (max)	220 V	Display type	LCD
Output frequency	50/60 Hz	International Protection (IP) code	IP20
Surge energy rating	1260 J	Operational conditions	
Heat dissipation	931 BTU/h	Operating temperature (T-T)	0 - 40 °C
Power factor	1	Storage temperature (T-T)	-15 - 45 °C
Output power factor	1	Operating relative humidity (H-H)	0 - 95%
Crest factor	3:1	Storage relative humidity (H-H)	0 - 95%
Emergency Power Off (EPO)	✓	Operating altitude	0 - 3048 m
Output voltage Total Harmonic Distortion (THD)	2%	Non-operating altitude	0 - 15240 m
Noise level	55 dB	Technical details	
Auto-restart	✓	Sustainability compliance	✓
Ports & interfaces		Sustainability certificates	Green Premium
AC outlet types	C13 coupler, C19 coupler	Compliance certificates	CE, RoHS
Power plug	Hardwire	Weight & dimensions	
AC outlets quantity	10 AC outlet(s)	Width	432 mm
USB port	✓	Depth	701 mm
Serial interface	✓	Height	86 mm
Serial ports quantity	1	Weight	29.2 kg
Battery		Package width	585 mm
Battery technology	Lithium-Ion (Li-Ion)	Package depth	984 mm

Battery

Battery voltage	180 V
Typical backup time at full load	5.25 min
Battery life (max)	10 year(s)

Weight & dimensions

Package height	392 mm
Package weight	38.5 kg

Other features

Nominal output voltage	230 V
Nominal input voltage	230 V



0731304435754



731304435754

Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.