

## **EZVIZ BC1 Smart Trio Pack Battery Camera**

## Brand : EZVIZ

Lens diameter

Product code: CS-BC1-B3

Product name : EZVIZ BC1 Smart Trio Pack Battery Camera

- 3x BC1 Cameras + 1x Base Station
- Up to 1 year of battery life on a single charge
- Secure the interior/exterior of your home for peace of mind
- Colour Night Vision for superior 24/7 security
- Built in Alarm Active Defence
- Compatible with Amazon Alexa, Google Assistant and IFTTT
- 2 years' warranty and 24/7 Tech Support

2 MP, 1/2.8" CMOS, FHD, Smart H.265, IR, DNR, WDR, IP 66, Wi-Fi, MicroSD, 12900 mAh, 5W, 3 pcs EZVIZ BC1 Smart Trio Pack Battery Camera. Type: IP security camera, Placement supported: Indoor & outdoor, Connectivity technology: Wired & Wireless. Mounting type: Wall, Product colour: White, Form factor: Turret. Lens viewing angle, horizontal: 108°, Lens viewing angle, diagonal: 128°. Sensor type: CMOS, Optical sensor size: 25.4 / 2.8 mm (1 / 2.8"), Number of effective pixels (H x V): 1920 x 1080 pixels. Lens diameter: 2.8 mm






Performance		Ports & interfaces	
Type *	IP security camera	Ethernet LAN (RJ-45) ports	1
Placement supported *	Indoor & outdoor	DC-in jack	1
Connectivity technology * Virtual assistant	Wired & Wireless	Security	
Day/night mode	Amazon Alexa & Apple Siri	Video motion detection	1
Antenna type	Internal	Detection distance	10 m
		Motion sensor	1
Design		Motion sensor technology	Passive infrared (PIR) sensor
Form factor * Mounting type *	Turret Wall	Management features	
Product colour *	White	Web-based management	✓
Housing material	Plastic	Web browser	1
Protection features	Dust resistant, Water resistant	Firmware upgradeable	1
International Protection (IP) code	IP66	Remotely operated	1
Weatherproof	1	Power	
Camera		Power source type *	AC, Battery
Lens viewing angle, horizontal	108°	Power consumption (typical)	5 W
Lens viewing angle, diagonal	128°	Power consumption (max)	5 W
Image sensor		DC output voltage	5
Number of sensors	1	Battery technology	Lithium
Optical sensor size	25.4 / 2.8 mm (1 / 2.8")	Battery capacity	12900 mAh
Progressive scan	1	Rechargeable battery	✓
Sensor type *	CMOS	Battery voltage	5 V
Number of effective pixels (H x V)	1920 x 1080 pixels	Operational conditions	
Lens system		Operating temperature (T-T)	-20 - 45 °C
Number of lenses *	1	Operating relative humidity (H-H)	0 - 95%

2.8 mm

Night vision		System requirements	
Night vision *	✓	Linux operating systems supported	<ul> <li>Image: A set of the set of the</li></ul>
Night vision distance	10 m	Weight & dimensions	
LED type	IR	Diameter	6.28 cm
Video		Length	104.8 mm
Maximum resolution *	1920 x 1080 pixels	Weight	851 g
Total megapixels *	2 MP H.265	Packaging data	
Video compression formats Supported graphics resolutions	1920 x 1080 (HD 1080)	Package width	293 mm
Supported video modes	1080p	Package depth	180 mm
Frame rate	30 fps	Package height	288 mm
Noise reduction	<ul> <li>Image: A set of the set of the</li></ul>	Package weight Package type	2.44 kg Box
Noise reduction technology	3D noise reduction	5 11	box
3D NR (Noise Reduction)	✓	Sustainability	
Full HD	✓	Sustainability certificates	UL ECOLOGO
Image quality adjustment	DNR	Compliance certificates	CE, REACH, RoHS, WEEE
Digital Wide Dynamic Range (DWDR)	<ul> <li>Image: A set of the set of the</li></ul>	Packaging content	
Audio		Number of cameras * Cables included	3 AC, USB
		Mounting kit	AC, 03B ✓
Built-in speaker(s)		Mounting brackets included	
Built-in microphone	<b>v</b>	Screws included	
Network		Manual	
Ethernet LAN *	1	AC adapter included	
Ethernet interface type	Gigabit Ethernet	Base included	
Wi-Fi *	<ul> <li>Image: A set of the set of the</li></ul>	Quick start guide	
Bluetooth *	×	Wall mounting kit	
Storage			•
Built-in HDD *	×	Other features	
Card reader integrated	✓	Magnetic base	1
Compatible memory cards	MicroSD (TransFlash)	Technical details	
Maximum memory card size	256 GB	Microphone type	Omnidirectional
		Integrated PIR sensor	1
		Lens mount interface	M12
		Logistics data	

Harmonized System (HS) code 85258900

Publication date: 19-DEC-2024. Prints or copies of Information are only valid on the printed Publication date



6941545602592

Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.