![EZVIZ logo]

EZVIZ C3X Luoti (muoto) IP-turvakamera Ulkona 1920 x 1080 pikseliä Katto/seinä

Tuotemerkki : EZVIZ

Tuotekoodi: CS-CV310-C0-6B22WFR

Tuotteen nimi : C3X

EZVIZ C3X. Malli: IP-turvakamera, Tuettu sijoitus: Ulkona, Yhteysteknologia: Langaton. Kiinnitystyyppi: Katto/seinä, Tuotteen väri: Valkoinen, Kotelo: Luoti (muoto). Pienin valaistus: 0,0005 lx, Objektiivin kuvakulma, vaakasuora: 89°, Objektiivin kuvakulma, kulmittain: 106°. Anturin tyyppi: CMOS, Optisen sensorin koko: 25,4 / 2,7 mm (1 / 2.7"). Kiinteä polttoväli: 4 mm

Performance

Type *	IP security camera
Placement supported *	Outdoor
Connectivity technology *	Wireless
Day/night mode	✔
Certification	UL / FCC / CE / WEEE / REACH

Design

Form factor *	Bullet
Mounting type *	Ceiling/wall
Product colour *	White
Protection features	Dust resistant, Water resistant
International Protection (IP) code	IP67

Camera

Camera pan control	✗
Camera tilt control	✗
Minimum illumination	0.0005 lx
Lens viewing angle, horizontal	89°
Lens viewing angle, diagonal	106°

Image sensor

Number of sensors	1
Optical sensor size	25.4 / 2.7 mm (1 / 2.7")
Progressive scan	✔
Sensor type *	CMOS

Lens system

Number of lenses *	1
Maximum aperture number	1.6
Fixed focal length	4 mm

Network

Ethernet LAN *	✔
Ethernet interface type	Fast Ethernet
Supported network protocols	64 / 128-bit WEP, WPA / WPA2, WPA-PSK / WPA2-PSK
Wi-Fi *	✔
Wi-Fi standards	802.11b, 802.11g, Wi-Fi 4 (802.11n)
Wi-Fi data rate (max)	144 Mbit/s
Bluetooth *	✗

Storage

Built-in HDD *	✗
Card reader integrated	✔
Compatible memory cards	MicroSD (TransFlash)
Maximum memory card size	256 GB

Ports & interfaces

Ethernet LAN (RJ-45) ports	1

Security

Video motion detection	✔
Security algorithms	64-bit WEP, 128-bit WEP, WPA, WPA-PSK, WPA2, WPA2-PSK

Power

Power consumption (max)	12 W
DC output voltage	12

Operational conditions

Operating temperature (T-T)	-30 - 60 °C
Operating relative humidity (H-H)	0 - 95%

Night vision

Night vision *	✔
Night vision distance	30 m
LED type	IR

Video

Maximum resolution *	1920 x 1080 pixels
Total megapixels *	2 MP
Video formats supported	H.264, H.265
Video compression formats	H.264, H.265
Supported video modes	1080p
Frame rate	25 fps
Noise reduction	✔
Noise reduction technology	3D noise reduction
Back Light Compensation (BLC)	✔
Digital Wide Dynamic Range (DWDR)	✔

Audio

Built-in speaker(s)	✔
Audio system	2-way
Built-in microphone	✔

Weight & dimensions

Width	72 mm
Depth	72 mm
Length	93.5 mm
Weight	425 g

Packaging data

Package width	253.5 mm
Package depth	111.5 mm
Package height	93.5 mm

Sustainability

Compliance certificates	RoHS

Packaging content

Number of cameras *	1
Mounting kit	✔
Screws included	✔
Manual	✔

Logistics data

Master (outer) case width	541 mm
Master (outer) case length	255 mm
Master (outer) case height	500 mm
Master (outer) case gross weight	16.8 kg
Products per master (outer) case	25 pc(s)

6971744238780

5060563451102