ASUS ROG Rapture GT6 (B-2-PK) Tri-band (2.4 GHz / 5 GHz / 5 GHz) Wi-Fi 6 (802.11ax) Black 4 Internal

Brand : ASUS

Product code: 90IG07F0-MU9A20

Product name : ROG Rapture GT6 (B-2-PK)

AX10000, 2.4GHz/5GHz, 574+4804 Mbps, 256MB, 512 DDR4, 3x RJ-45, 1 x 2.5 Gigabit WAN Port, Wi-Fi 6 ASUS ROG Rapture GT6 (B-2-PK). Product colour: Black, Antenna type: Internal, Product type: Mesh router. Wi-Fi band: Tri-band (2.4 GHz / 5 GHz / 5 GHz), Top Wi-Fi standard: Wi-Fi 6 (802.11ax), Wi-Fi standards: 802.11a, 802.11b, 802.11g, Wi-Fi 4 (802.11n), Wi-Fi 5 (802.11ac), Wi-Fi 6 (802.11ax). Processor frequency: 1.7 GHz, Internal memory: 512 MB, Flash memory: 256 MB. AC input voltage: 110 - 240 V, AC input frequency: 50 - 60 Hz, AC adapter output voltage: 19 V. Width: 172.3 mm, Depth: 78.1 mm, Height: 176.8 mm

Design

Product type	Mesh router
Product colour *	Black
LED indicators	Power
Antenna type *	Internal
Antennas quantity	9
Maximum coverage	538.8 m²
Reset button	✔

Wireless LAN features

Wi-Fi band *	Tri-band (2.4 GHz / 5 GHz / 5 GHz)
Top Wi-Fi standard *	Wi-Fi 6 (802.11ax)
Wi-Fi standards	802.11a, 802.11b, 802.11g, Wi-Fi 4 (802.11n), Wi-Fi 5 (802.11ac), Wi-Fi 6 (802.11ax)
WLAN data transfer rate (first band)	574 Mbit/s
WLAN data transfer rate (second band)	4804 Mbit/s
WLAN data transfer rate (third band)	4804 Mbit/s
Networking standards	IEEE 802.11a, IEEE 802.11b, IEEE 802.11g, IEEE 802.11n
Security algorithms	WPA, WPA-Enterprise, WPA2, WPA2-Enterprise, WPA3
Point-to-point protocol over Ethernet (PPPoE)	✔
IGMP snooping	✔
Dynamic DNS (DDNS)	✔
VPN support	VPN Client L2TP VPN Client OVPN VPN Client PPTP VPN Client WireGuard VPN Server IPSec VPN Server OVPN VPN Server PPTP VPN Server WireGuard VPN Fusion

Features

Built-in processor	✔
Processor cores	3
Processor frequency	1.7 GHz

Features

Internal memory	512 MB
Flash memory	256 MB
Quality of Service (QoS) support	✔
BeamForming	✔
DHCP server	✔
Parental control	✔
SSID Broadcast	✔
MU-MIMO technology	✔

Ports & interfaces

Ethernet LAN (RJ-45) ports *	4
Ethernet WAN	✔
DC-in jack	✔

Power

AC input voltage	110 - 240 V
AC input frequency	50 - 60 Hz
AC adapter output voltage	19 V
AC adapter output current	2.37 A

Weight & dimensions

Width	172.3 mm
Depth	78.1 mm
Height	176.8 mm
Weight	880 g

Packaging content

Number of products included	2 pc(s)
Ethernet cable	✔

Packaging data

Package width	425 mm
Package depth	140 mm
Package height	280 mm
Package weight	3.72 kg

4711081798569