




MSI PRO B760M-G DDR4 emolevy Intel B760 LGA 1700 mikro ATX

Tuotemerkki : MSI

Tuotekoodi: PRO B760M-G DDR4

Tuotteen nimi : PRO B760M-G DDR4

MSI PRO B760M-G DDR4. Suoritinvalmistaja: Intel, Prosessorin kanta: LGA 1700, Yhteensopivat prosessorit: Intel® Celeron®, Intel® Pentium® Gold. Tuetut muistityypit: DDR4-SDRAM, Sisäinen enimmäismuisti: 64 GB, Muistipaikkojen tyyppi: DIMM. Tuetut tallennusasemaliitännät: M.2, SATA III, RAID-tasot: 0, 1, 5, 10. Ethernet-liitännän tyyppi: 2.5 Gigabit Ethernet. Komponentti (tuotteelle): PC, Emolevyn muototekijä: mikro ATX, Emolevyn piirisarjan perhe: Intel



Processor		Rear panel I/O ports	
Processor manufacturer *	Intel	USB 2.0 ports quantity *	2
Processor socket *	LGA 1700	USB 3.2 Gen 1 (3.1 Gen 1) Type-A ports quantity *	4
Compatible processor series *	Intel® Celeron®, Intel® Pentium® Gold	Ethernet LAN (RJ-45) ports *	1
Maximum number of SMP processors	1	VGA (D-Sub) ports quantity *	1
Supported processor sockets	LGA 1700	HDMI ports quantity *	1
Memory		HDMI version	2.1
Supported memory types *	DDR4-SDRAM	DisplayPorts quantity	1
Number of memory slots *	2	DisplayPort version	1.4
Memory slots type	DIMM	Network	
Memory channels	Dual-channel	Ethernet LAN	✓
ECC compatibility	Non-ECC	Ethernet interface type	2.5 Gigabit Ethernet
Supported memory clock speeds	4800, 4600, 4400, 4266, 4200, 4000, 3800, 3733, 3600, 3466, 3400, 3333, 3200, 2933, 2666, 2400, 2133 MHz	Wi-Fi *	✗
		Features	
Supported memory clock speed (max)	4800 MHz	Motherboard chipset *	Intel B760
Maximum internal memory *	64 GB	Audio chip	Realtek ALC897
Storage controllers		Audio output channels *	7.1 channels
Supported storage drive interfaces *	M.2, SATA III	Component for *	PC
RAID support	✓	Motherboard form factor *	micro ATX
RAID levels	0, 1, 5, 10	Motherboard chipset family *	Intel
Internal I/O		Power source type	ATX
USB 2.0 connectors *	4	Windows operating systems supported	Windows 10, Windows 11
USB 3.2 Gen 1 (3.1 Gen 1) connectors *	2	Expansion slots	
Number of SATA III connectors *	4	PCI Express x1 (Gen 3.x) slots	2
Front panel audio connector	✓	BIOS	
Front panel connector	✓	BIOS type *	UEFI AMI
ATX Power connector (24-pin)	✓	BIOS memory size	256 Mbit
CPU fan connector	✓	System Management BIOS (SMBIOS) version	3.5

Internal I/O		Weight & dimensions	
TPM connector	✓	Width	220 mm
RGB LED pin header	✓	Depth	243.8 mm



4711377027366

Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.

Publication date: 22-MAR-2025. Prints or copies of Information are only valid on the printed Publication date