MSI MAG CORELIQUID 280R V2 Tietokoneen jäähdytysjärjestelmä Tietokonekotelo Jäähdytin 14 cm musta

Tuotemerkki : MSI Tuotekoodi: MAG CORELIQUID 280R V2

Tuotteen nimi: MAG CORELIQUID 280R V2

MSI MAG CORELIQUID 280R V2. Malli: Jäähdytin, Tuulettimen halkaisija: 14 cm, Pyörimisnopeus (min.): 500 RPM, Pyörimisnopeus (maks.): 1800 RPM, Melutaso (alhainen nopeus): 14,8 dB, Melutaso (korkea nopeus): 33,28 dB, Suurin ilmavirtaus: 84,36 cfm, Suurin ilmanpaine: 2,29 mmH2O, Laakerityyppi: Kuulalaakeri. Tuotteen väri: musta





Performance		Performance	
Suitable location *	Computer case Cooler	Pump motor speed	4200 RPM 500 RPM
Type * Fan diameter	Cooler 14 cm	Fan speed (min) Fan speed (max)	1800 RPM
Supported processor sockets	LGA 1150 (Socket H3), LGA 1151 (Socket H4), LGA 1155 (Socket H2), LGA 1156 (Socket H2), LGA 1156 (Socket H5), LGA 1700, LGA 2011 (Socket B), LGA 2011-v3 (Socket R), LGA 2011-v3 (Socket R), LGA 2066, Socket AM2, Socket AM2+, Socket AM4, Socket FM1, Socket FM2, Socket FM2+	Product colour * Material Radiator material Number of fans Illumination LED Illumination colour	Black Aluminium Aluminum 2 fan(s) Blue, Pink
Rotational speed (min)	500 RPM	Fan connector	4-pin + 4-pin
Rotational speed (max)	1800 RPM	Power	
Noise level (low speed) Noise level (high speed) Maximum airflow Maximum air pressure Fan diameter 2 Fan 2 rotational speed (min) Fan 2 rotational speed (max) Fan 2 noise level (low speed) Fan 2 noise level (high speed) Fan 2 maximum airflow Fan 2 maximum air pressure Pulse-width modulation (PWM)	14.8 dB 33.28 dB 84.36 cfm 2.29 mmH2O 14 cm 500 RPM 1800 RPM 14.8 dB 33.28 dB 84.36 cfm 2.29 mmH2O	Fan power consumption Pump power consumption Rated current Pump voltage Pump current Fan voltage Fan current Weight & dimensions Radiator width Radiator depth Radiator height	2.28 W 4.08 W 0.19 A 12 V 0.34 mA 12 V 0.19 A 31.2 cm 2.7 cm 14 cm
support	✓	Fan dimensions (W x D x H)	140 x 140 x 25 mm
Bearing type Fan noise level (min) Fan noise level (max) Fan bearing technology Pump connector	Ball bearing 14.8 dB 33.28 dB Ball bearing 4-pin	Logistics data Harmonized System (HS) code	84733080



4719072864095

Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.