MSI MPG CORELIQUID K240 V2 Tietokoneen jäähdytysjärjestelmä Tietokonekotelo Jäähdytyssetti 12 cm musta

Tuotemerkki : MSI Tuotekoodi: MPG CORELIQUID K240 V2

Tuotteen nimi: MPG CORELIQUID K240 V2

MSI MPG CORELIQUID K240 V2. Malli: Jäähdytyssetti, Tuulettimen halkaisija: 12 cm, Pyörimisnopeus (min.): 0 RPM, Pyörimisnopeus (maks.): 2500 RPM, Melutaso (korkea nopeus): 39,9 dB, Suurin ilmavirtaus: 77,4 cfm, Suurin ilmanpaine: 4,29 mmH2O, Laakerityyppi: Kuulalaakeri. Tuotteen väri: musta





Performance		Performance	
Suitable location *	Computer case	Pump motor speed (max)	3100 RPM
Type *	Cooling set	Fan speed (min)	0 RPM
Fan diameter	12 cm	Fan speed (max)	2500 RPM
Supported processor sockets	LGA 1150 (Socket H3), LGA 1151 (Socket H4), LGA 1155 (Socket H2), LGA 1156 (Socket H2), LGA 1156 (Socket H3), LGA 1200 (Socket H5), LGA 1366 (Socket B), LGA 1700, LGA 2011 (Socket R), LGA 2011-v3 (Socket R), LGA 2066, Socket AM2, Socket AM2+, Socket AM3, Socket AM3+, Socket AM4, Socket FM1, Socket FM2, Socket	Design	D
		Product colour *	Black
		Material	Mesh, Rubber
		Radiator material	Aluminum
		Number of fans	2 fan(s)
		Illumination LED	•
	FM2+	Number of LEDs	1
Rotational speed (min)	0 RPM	Power	
Rotational speed (max)	2500 RPM	Fan power consumption	3.36 W
Noise level (high speed)	39.9 dB	Pump power consumption	4 W
Maximum airflow	77.4 cfm	Pump voltage	12 V
Maximum air pressure	4.29 mmH2O	Pump current	0.33 mA
Fan diameter 2	12 cm	Fan current	0.28 A
Fan 2 rotational speed (min)	0 RPM	W. C. D. C. P	
Fan 2 rotational speed (max)	2500 RPM	Weight & dimensions	
Fan 2 noise level (high speed)	39.9 dB	Radiator width	24.3 cm
Fan 2 maximum airflow	77.4 cfm	Radiator depth	40.6 cm
Fan 2 maximum air pressure	4.29 mmH2O	Radiator height	14.6 cm
Pulse-width modulation (PWM)	√	Pump width	9.47 cm
support		Pump depth	9.4 cm
Bearing type	Ball bearing	Pump height	8.34 cm
Fan noise level (max)	39.9 dB	Fan dimensions (W x D x H)	120 x 120 x 25 mm
Pump noise level	20 dB	Logistics data	
Fan bearing technology	Double ball bearing	Harmonized System (HS) code	84733080
Pump connector	4-pin	namonized System (113) code	31,33000
Pump motor speed	2800 RPM		
Pump motor speed (min)	2500 RPM		





4719072862862

4526541039058

Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.