



kramer

PT-3U

Active USB 3.0 Extender



PT-3U is an innovative active USB 3.0 extender that extends the USB cable distance between the host and the device by reclocking and equalizing the USB signal. Placing PT-3U in the transmission path, removes dropout and digital noise (sparkles) in your installation that may result from using long USB cables

FEATURES

- True Plug & Play - No additional driver program is needed
- USB 3.0 Super Speed (5Gbps) Standard - Compliant with USB 3.0
- Backwards Compatible - USB 2.0, 1.1
- Optional external power supply
- Buffers incoming & outgoing signal
- Certifications - CE, FCC, REACH, ROHS



kramer

TECHNICAL SPECIFICATIONS

Inputs	USB 3.0 On a USB type-A female connector
Outputs	USB 3.0 On a USB type-A female connector
General	Max. Data Rate: 5Gbps Max. Range: 5Gbps — 4.85m, 3m to PT-3U, 1.85m to Device Backwards Compatibility USB 2.0, 1.1
Power	Consumption: 0.13W
Environmental Conditions	Operating Temperature: 0-60°C Operating Humidity: 10%-80% Storage Temperature: -20-70°C Storage Humidity: 10%-80%
Product Dimensions	2.60cm x 5.80cm x 2.00cm (1.02" x 2.28" x 0.79") W, D, H
Product Weight	0.0kg (0.1lbs) approx
Shipping Dimensions	12.60cm x 8.40cm x 4.10cm (4.96" x 3.31" x 1.61") W, D, H
Shipping Weight	0.1kg (0.2lbs) approx