Tuotteen nimi: OH46B-S

Samsung OH46B-S Digitaalinen litteä infotaulu 116,8 cm (46") LCD 3500 cd/m² Full HD musta Sisäänrakennettu prosessori Tizen 6.5 24/7

Tuotemerkki: Samsung Tuoteperhe: OHB-S **Tuotekoodi:**

LH46OHBESGBXEN

Samsung OH46B-S. Tuotteen muotoilu: Digitaalinen litteä infotaulu. Näytön halkaisija: 116,8 cm (46"), Näytön teknologia: LCD, Näytön erottelutarkkuus: 1920 x 1080 pikseliä, Näytön kirkkaus: 3500 cd/m², HD-tyyppi: Full HD. Toiminta-aika (tunteja/päiviä): 24/7. Käyttöjärjestelmä asennettu: Tizen 6.5. Tuotteen väri: musta





Display		Design	
Panel type Display diagonal * Display technology * Display resolution * Display brightness *	VA 116.8 cm (46") LCD 1920 x 1080 pixels 3500 cd/m ²	Panel mounting interface Bezel width (bottom) Bezel width (side) Bezel width (top) Bezel colour	995 x 500 mm 2.49 cm 2.49 cm 2.49 cm Black
HD type * Touchscreen * Response time Contrast ratio (typical) Dynamic contrast ratio marketing	Full HD X 6 ms 6000:1 Mega Contrast	Performance Purpose * Operating hours (hours/days) HDCP HDCP version	Universal 24/7 ✓ 2.2
name Viewing angle, horizontal	178°	Power	-:-
Viewing angle, vertical Pixel pitch Horizontal scan range Vertical scan range	178° 0.53 x 0.53 mm 15 - 135 kHz 24 - 75 Hz	Power consumption (typical) * Power consumption (sleep) AC input voltage AC input frequency	430 W 0.5 W 100 - 240 V 50 - 60 Hz
Glass thickness	5 mm	Computer system	
Glass film RGB colour space Colour gamut	AG/AR Film NTSC 72%	Computer system * Computer system type	✓ System on Chip (SoC)
Ports & interfaces		Built-in processor *	✓
HDMI ports quantity * HDMI version DVI port * USB port * USB ports quantity	2 2.0 × •	Operating system installed Weight & dimensions Display width Display depth Display height	Tizen 6.5 1069 mm 85 mm 623.6 mm
Ethernet LAN *	<u>-</u> ✓	Display weight	36 kg
Ethernet LAN (RJ-45) ports	2	Packaging data	
Wi-Fi * Audio (L/R) out RS-232 interface	x 1	Package width Package depth Package height	1156 mm 200 mm 713 mm
Audio		Package weight	40.5 kg
Built-in speaker(s) *	×	Operational conditions Operating temperature (T-T)	-30 - 50 °C

Design		Operational conditions	
Product design * Di	Digital signage flat panel Horizontal/Vertical Black Flat ✓	Operating relative humidity (H-H)	10 - 80%
Orientation		Certificates	
Screen shape		Certification	Class A 60950-1, 62368-1
		Other features	
		Flash memory	8000 MB
		Glass protection	✓



8806094726541

Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.