KYOCERA ECOSYS PA2100cwx Väri 1200 x 1200 DPI A4 Wi-Fi

Tuotemerkki: KYOCERA Tuoteperhe: ECOSYS Tuotekoodi: 110C093NL0

Tuotteen nimi: PA2100cwx

KYOCERA ECOSYS PA2100cwx. Tulostustekniikka: Laser, Väri. Värikasettien määrä: 4, Suurin toimintajakso: 65000 sivua kuukaudessa. Suurin resoluutio: 1200 x 1200 DPI. Suurin ISO A-luokan paperikoko: A4. Tulostusnopeus (musta, normaalilaatu, A4/US Letter): 21 ppm, Kaksipuolinen tulostus. Näyttö: LCD. Verkkovalmius, Wi-Fi. Tuotteen väri: musta, Valkoinen





Printing		Network	
Printing Print speed (colour, normal quality, A4/US Letter) Colour * Print technology * Duplex printing * Maximum resolution * Print speed (black, normal quality, A4/US Letter) * Warm-up time Time to first page (black, normal) Time to first page (colour, normal) Print margins (top, bottom, right, left)	21 ppm Laser 1200 x 1200 DPI 21 ppm 32 s 11 s 12.5 s 4.2 mm	Network Network ready Wi-Fi * Ethernet LAN * Cabling technology Ethernet LAN data rates Wi-Fi standards Near Field Communication (NFC) Bluetooth Mobile printing technologies Performance	10/100/1000Base-T(X) 10,100,1000 Mbit/s 802.11b, 802.11g, Wi-Fi 4 (802.11n) X Apple AirPrint, Kyocera Mobile Print, Mopria Print Service
Watermark printing Secure printing N-up printing Booklet printing function Economical printing	✓ ✓ 2, 4, 6, 8, 9, 16, 25 ×	Internal memory * Maximum internal memory Card reader integrated Built-in processor Processor family Processor frequency	512 MB 512 MB X ARM Cortex 800 MHz
Features Maximum duty cycle *	65000 pages per month	Sound pressure level (printing) Sound power level (standby)	48 dB 30 dB
Recommended duty cycle Printing colours * Number of print cartridges * Page description languages * Printer fonts Country of origin	500 - 1500 pages per month Black, Cyan, Magenta, Yellow 4 PCL 6, PDF, PostScript 3, XPS PCL, PostScript China	Design Market positioning * Product colour * Built-in display * Display Touchscreen Display number of lines Control type	Home & office Black, White LCD X 2 lines Buttons

Features		Design	
Replacement cartridges	TK-5430K Zwart (toner 1.250) ISO/IEC 19798 TK-5430Y Geel (toner 1.250) ISO/IEC 19798 TK-5430M Magenta (toner 1.250) ISO/IEC 19798 TK-5430C Cyaan (toner 1.250) ISO/IEC 19798 TK-5440K Zwart (toner 2.800) ISO/IEC 19798 TK-5440Y Geel (toner 2.400) ISO/IEC 19798 TK-5440M Magenta (toner 2.400) ISO/IEC 19798 TK-5440M ISO/IEC 19798 TK-5440C Cyaan (toner 2.400) ISO/IEC 19798	Certification	GS, TUV
		Certificates	
		Waste Electrical and Electronic Equipment (WEEE) compliance	✓
		Power	
		Power consumption (printing) *	345 W
		Power consumption (ready)	33 W
		Power consumption (PowerSave)	0.9 W
Input & output capacity		Power consumption (off)	0.2 W
Total number of input trays *	2	Energy Star Typical Electricity Consumption (TEC)	0.691 kWh/week
Total input capacity *	300 sheets	AC input voltage	220 - 240 V
Total output capacity * Paper tray 1 input capacity	150 sheets 250 sheets	AC input frequency	50 - 60 Hz
Multi-Purpose tray	∠30 sileets	System requirements	
Multi-Purpose tray input capacity	50 sheets	Windows operating systems	
Maximum number of input trays	2	supported	✓
Maximum input capacity	550 sheets	Mac operating systems supported	✓
Maximum output capacity	150 sheets	Linux operating systems supported	✓
Paper handling		Weight & dimensions	
Maximum ISO A-series paper size *	A4	Width	410 mm
Maximum print size	216 x 356 mm	Depth	410 mm
Paper tray media types *	Plain paper	Height	329 mm
Multi-purpose tray media types	Plain paper	Weight	26 kg
ISO A-series sizes (A0A9) *	A4, A5, A6	Packaging data	
ISO B-series sizes (B0B9)	B5, B6	Package width	592 mm
Non-ISO print media sizes Custom media width	Legal, Letter 70 - 216 mm	Package depth	567 mm
Custom media length	148 - 356 mm	Package height	460 mm
Paper tray media weight	60 - 163 g/m ²	Package weight	27 kg
Multi-Purpose Tray media weight	60 - 220 g/m²	Packaging content	
Duplex media weight	60 - 120 g/m²	Cartridge(s) included	✓
Ports & interfaces		Included cartridge capacity (black)	1500 pages
Standard interfaces	Ethernet, USB 2.0, Wireless LAN	Included cartridge capacity (CMY)	1500 pages
Direct printing *		Cables included	AC
USB port *		Logistics data	
USB 2.0 ports quantity	1	Harmonized System (HS) code	84433210
USB connector	USB Type-A	Technical details	
		Compliance certificates	CE
		•	









Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.