

KYOCERA PA6000x 1200 x 1200 DPI A4

Tuotemerkki : KYOCERA

Tuotekoodi: 110COT3NL0

Tuotteen nimi : PA6000x

KYOCERA PA6000x. Tulostustekniikka: Laser. Värikasettien määrä: 1, Suurin toimintajakso: 300000 sivua kuukaudessa. Suurin resoluutio: 1200 x 1200 DPI. Suurin ISO A-luokan paperikoko: A4. Tulostusnopeus (musta, normaalilaatu, A4/US Letter): 60 ppm, Kaksipuolinen tulostus. Näyttö: LCD. Verkkovalmius. Tuotteen väri: Valkoinen



Printing		Network	
Duplex printing mode	Auto	Ethernet LAN data rates	10,100,1000 Mbit/s
Print resolution black	1200 x 1200 DPI	Near Field Communication (NFC)	✗
Colour *	✗	Bluetooth	✗
Print technology *	Laser	Security algorithms	HTTPS, IPPS, IPsec, SNMPv3
Duplex printing *	✓	Mobile printing technologies	Apple AirPrint, Google Cloud Print, Kyocera Mobile Print, Mopria Print Service
Maximum resolution *	1200 x 1200 DPI		
Print speed (black, normal quality, A4/US Letter) *	60 ppm	Performance	
Duplex print speed (black, normal quality, A4/US Letter)	43 ppm	Internal memory *	512 MB
Warm-up time	25 s	Maximum internal memory	2500 MB
Time to first page (black, normal)	4.55 s	Compatible memory cards	SD, SDHC
Features		Built-in processor	✓
Maximum duty cycle *	300000 pages per month	Processor family	ARM Cortex
Recommended duty cycle	15000 - 30000 pages per month	Processor model	Cortex-A53
Printing colours *	Black	Processor frequency	1400 MHz
Number of print cartridges *	1	Processor cores	2
Page description languages *	Epson LQ, IBM ProPrinter, JPEG, OpenXPS, PCL 5e, PCL 6, PCL XL, PCLm, PDF, PWG, PostScript 3, TIFF, URF, XPS	Sound pressure level (printing)	57 dB
Printer fonts	Barcode, Bitmap, PCL	Sound power level (standby)	33 dB
Number of printer fonts	93	Design	
Replacement cartridges	TK-3440	Market positioning *	Business
Input & output capacity		Product colour *	White
Total number of input trays *	1	Built-in display *	✓
Total input capacity *	500 sheets	Display	LCD
Total output capacity *	500 sheets	Colour display	✗
Paper tray 1 input capacity	500 sheets	Touchscreen	✗
Paper input type	Cassette, Paper tray	Display number of lines	5 lines
Multi-Purpose tray	✓	Control type	Buttons
Multi-Purpose tray input capacity	100 sheets	Certification	GS, TÜV, CE
Maximum number of input trays	5	Power	
Maximum input capacity	2600 sheets	Power consumption (printing) *	710.2 W
Maximum output capacity	500 sheets	Power consumption (standby)	9 W
Paper handling		Power consumption (PowerSave)	0.5 W
Maximum ISO A-series paper size *	A4	AC input voltage	220 - 240 V
Maximum print size	216 x 356 mm	AC input frequency	50 - 60 Hz
Paper tray media types *	Plain paper	System requirements	
Multi-purpose tray media types	Legal, Letter	Windows operating systems supported	✓
ISO A-series sizes (A0...A9) *	A4, A5		
ISO B-series sizes (B0...B9)	B5		

Paper handling		System requirements	
Non-ISO print media sizes	Legal, Letter	Mac operating systems supported	Mac OS X 10.10 Yosemite, Mac OS X 10.11 El Capitan, Mac OS X 10.12 Sierra, Mac OS X 10.13 High Sierra, Mac OS X 10.14 Mojave, Mac OS X 10.15 Catalina, Mac OS X 10.15.3 Catalina, Mac OS X 10.9 Mavericks, Mac OS X 11.0 Big Sur, Mac OS X 12.0 Monterey, Mac OS X 13.0 Ventura
Custom media width	140 - 216 mm		
Custom media length	210 - 356 mm		
Paper tray media weight	60 - 120 g/m ²		
Multi-Purpose Tray media weight	60 - 220 g/m ²		
Duplex media weight	60 - 120 g/m ²	Linux operating systems supported	✓
Ports & interfaces		Other operating systems supported	ChromeOS
Standard interfaces	RJ-45, USB 2.0	Sustainability	
Direct printing *	✓	Sustainability certificates	Blue Angel, ENERGY STAR, EPEAT Silver
USB port *	✓	Weight & dimensions	
USB 2.0 ports quantity	2	Width	410 mm
USB connector	USB Type-A / USB Type-B	Depth	416 mm
Optional connectivity	Ethernet, Parallel, Wireless LAN	Height	363 mm
Network		Weight	16.2 kg
Network ready	✓	Packaging data	
Wi-Fi *	✗	Package width	549 mm
Ethernet LAN *	✓	Package depth	517 mm
Cabling technology	10/100/1000Base-T(X)	Package height	455 mm
		Package weight	20 kg
		Packaging content	
		Cartridge(s) included	✓
		Included cartridge capacity (black)	11000 pages
		Cables included	AC
		Technical details	
		Compliance certificates	CE, REACH, RoHS



0632983079904



632983079904

Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.