



Lenovo ThinkPad 90W Ultra Dock Docking Black

Brand : Lenovo

Product code: 40A20090SA

Product name : ThinkPad 90W Ultra Dock



- 3 x USB 2.0 and 3 x USB 3.0 with one always-on to charge mobile devices
 - 10/1000 Gigabit Ethernet supporting enterprise manageability features
 - Supports up to 3 external monitos
- ThinkPad Ultra Dock, 90W, Black

Lenovo ThinkPad 90W Ultra Dock Docking Black:

With a single eject button the ThinkPad Ultra Dock includes a wide range of video, display and connectivity ports, so you can multi-task and be productive like never before. A variety of USB 2.0 and USB 3.0 ports provide connectivity and power for all your productivity accessories, including an always-on port for mobile device charging any time, even when your laptop's not present. Connect up to three monitors for the ultimate in workplace efficiency, and it's made for large enterprises with no-hassle, peace of mind features like MAC address pass-through and PXE boot, and has a lock slot for physical security. Driver-free, this dock delivers crystal clear video quality thanks to Lenovo technology to make office work convenient, easy, and productive.

Ports & interfaces		Performance	
Connectivity technology *	Docking	Maximum refresh rate	60 Hz
USB 2.0 ports quantity *	3	Cable lock slot	✓
USB 3.2 Gen 1 (3.1 Gen 1) Type-A ports quantity *	3	Product colour *	Black
USB Power Delivery	✓	Brand compatibility	Lenovo
USB Power Delivery up to	65 W	Compatibility	ThinkPad
HDMI ports quantity *	1	Certification	GOST (Russia),BSMI,EC-DoC,CE,UL,FCC,KC (Korea),UkrSEPRO,CB,NOM,sDOC,AS/NZS DoC,VCCI
HDMI version	1.4		
VGA (D-Sub) ports quantity	1		
DisplayPorts quantity	2		
DVI-D ports quantity	1		
Combo headphone/mic port	✓		
Headphone outputs *	1		
DC-in jack	✓		
Network		Power	
Ethernet LAN *	✓	Power consumption (typical)	90 W
Ethernet LAN (RJ-45) ports	1		
Ethernet LAN data rates	10,100,1000 Mbit/s		
Performance		Software	
Card reader integrated *	✗	Windows operating systems supported	Windows 10, Windows 7, Windows 8, Windows 8.1
HD type	4K Ultra HD		
Maximum digital resolution	3840 x 2160 pixels		
Number of displays supported	3		
		Operational conditions	
		Operating temperature (T-T)	5 - 43 °C
		Operating relative humidity (H-H)	5 - 95%
		Weight & dimensions	
		Width	345 mm
		Depth	162.5 mm
		Height	55.6 mm
		Weight	920 g
		Packaging content	
		Quick start guide	✓

Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.

Publication date: 21-SEP-2024. Prints or copies of Information are only valid on the printed Publication date