

Fujitsu RC25 telinekonsoli 43,2 cm (17") 1280 x 1024 pikseliä Harmaa 1U

Tuotemerkki : Fujitsu **Tuotekoodi:** S26361-K1387-V300

Tuotteen nimi: RC25

Fujitsu RC25. Näytön halkaisija: 43,2 cm (17"), Näytön erottelutarkkuus: 1280 x 1024 pikseliä, Näyttö: TFT. Skannausalue (vaaka): 30 - 61 kHz, Skannausalue (pysty): 55 - 75 Hz. Näppäimistön kieli: Englanti (UK), Näppäimistön asettelu: QWERTY. Sertifiointi: CB, WEEE, CE, EN. Virrankulutus: 30 W, Virrankulutus valmiustilassa: 3 W, AC-adapterin syöttöjännite: 100 - 240 V





Display		Technical details	
Display TFT Display brightness 250 cd/m² Contrast ratio (typical) 450:1 Viewing angle, horizontal 80° Viewing angle, vertical 80° On Screen Display (OSD) Pixel pitch 0.26 x 0.26 m Aspect ratio 4:3	1280 x 1024 pixels TFT	Compliance certificates Rack capacity	RoHS 1U
		Keyboard	
	450:1 80°	Built-in touchpad Keyboard language Keyboard layout	UK English QWERTY
	√ 0.26 x 0.26 mm	Certificates	
		Certification	CB, WEEE, CE, EN
		Power	
Response time Display number of colours		Power consumption (typical) Power consumption (standby)	30 W 3 W
Scanning frequency		AC adapter input voltage	100 - 240 V
Horizontal scan range	30 - 61 kHz	AC adapter frequency	50/60 Hz
Vertical scan range	55 - 75 Hz	Operational conditions	
Technical details Mean time between failures (MTBF) Height (in Rack Units) Size (imperial) Product colour Operating relative humidity (H-H)	50000 h 1 48.3 cm (19") Grey 20 - 80%	Operating temperature (T-T) Storage temperature (T-T)	10 - 35 °C -20 - 60 °C
		Weight & dimensions	
		Width Height Depth Weight	486 mm 42.5 mm 444 mm 14 kg
		Packaging data	
		Package dimensions (WxDxH)	540 x 940 x 170 mm

