


BenQ MW560 dataprojektori Vakioprojektori 4000 ANSI lumenia DLP WXGA (1280x800) 3D Valkoinen

Tuotemerkki : BenQ Tuotekoodi: 9H.JNF77.1JE

Tuotteen nimi: MW560







| Projector | | Ports & interfaces | |
|--|---|-----------------------------------|---|
| Smart projector * | × | Composite video in * | 1 |
| Screen size compatibility * | 1524 - 3810 mm (60 - 150") | DVI port * | × |
| Projector brightness * | 4000 ANSI lumens DLP WXGA (1280x800) 20000:1 | AC (power) in | ✓ |
| Projection technology * Projector native resolution * Contrast ratio (typical) * | | Network | |
| | | Smart TV * | × |
| Native aspect ratio * | 16:10 | Ethernet LAN * | × |
| Number of colours Horizontal scan range Vertical scan range | 1.07 billion colours 15 - 102 kHz 23 - 120 Hz | Wi-Fi * | × |
| | | Storage | |
| Keystone correction, vertical | -40 - 40° | Card reader integrated * | × |
| Matrix size | 1.65 cm (0.65") | Features | |
| Light source | | Noise level (economic mode) | 29 dB |
| Light source type * | Lamp | On Screen Display (OSD) | ✓ |
| Service life of light source * | 6000 h | | Arabic, Bulgarian, Simplified Chinese, Traditional Chinese, Croatian, Czech, Danish, German, Dutch, English, Spanish, Finnish, French, Greek, Hindi, Hungarian, Italian, Japanese, Korean, Polish, Portuguese, Romanian, Russian, |
| Service life of light source (economic mode) | 10000 h | | |
| Lens system | | On Screen Display (OSD) languages | |
| Focal length range | 22 - 24.1 mm | | |
| Aperture range (F-F) | 2.56 - 2.68 | | Swedish, Thai, Turkish, Vietnamese |
| Zoom capability | ✓ | Number of OSD languages | 30 |
| Zoom ratio | 1.1:1 | Noise level * | 34 dB |
| Throw ratio | 1.55~1.7:1 | Multimedia | |
| Offset | 100% | Built-in speaker(s) * | ✓ |
| Video | | RMS rated power | 10 W |
| Analog signal format system * | NTSC, PAL, SECAM | Number of built-in speakers 1 | 1 |
| Full HD * | × | | |

| Video | | Design | |
|---|---|--|--|
| 3D * Supported graphics resolutions Supported video modes | . (WUXGA) 480i 480n 576i 576n 720n 1080i | | Presentation Standard throw projector White ✓ |
| Video colour modes | Presentation, sRGB | Cable lock slot type | Kensington |
| Ports & interfaces HDMI connector type S-Video inputs quantity USB 2.0 ports quantity Mini-USB 2.0 ports quantity Headphone outputs Microphone in Serial interface type * PC in (D-Sub) VGA (D-Sub) ports quantity * HDMI ports quantity * | Full-size 1 1 1 1 1 1 2 RS-232 | Power Power source * Power consumption (typical) * Power consumption (standby) * Power consumption (max) Power consumption (economy mode) AC input voltage Operational conditions Operating temperature (T-T) Weight & dimensions Width Depth | AC 260 W 0.5 W 280 W 215 W 100 - 240 V 0 - 40 °C |
| | | Depth Height Weight * Packaging content | 221 mm 120 mm 2.3 kg |
| | | Remote control included * Remote control type Cables included | ✓ IR AC, VGA |

