## D-Link DMS-107/E verkkokytkin Hallitsematon Gigabit Ethernet (10/100/1000) musta

Tuotemerkki : D-Link

Tuotekoodi: DMS-107/E

Tuotteen nimi : DMS-107/E

D-Link DMS-107/E. Kytkin tyyppi: Hallitsematon. Peruskytkentä RJ-45 Ethernet-porttien tyyppi: Gigabit Ethernet (10/100/1000), Basic kytkentä RJ-45 Ethernet-porttien määrä: 5. MAC-osoitetaulukko: 2000 entries, Kytkentäkapasiteetti: 20 Gbit/s. Verkkostandardit: IEEE 802.1p, IEEE 802.3, IEEE 802.3ab, IEEE 802.3az, IEEE 802.3bz, IEEE 802.3u, IEEE 802.3x. DC-syöttöjännite: 12 V





Management features		Design	
Switch type *	Unmanaged	Housing material	Metal
Quality of Service (QoS) support	1	LED indicators	Activity, Link, Power
Ports & interfaces		Performance	
Basic switching RJ-45 Ethernet ports quantity *	5	Fanless Mean time between failures (MTBF)	✔ 944277.78 h
Basic switching RJ-45 Ethernet ports type *	Gigabit Ethernet (10/100/1000)	Power	
Gigabit Ethernet (copper) ports quantity 2.5G Ethernet (copper) ports	5	Power source * DC input voltage	DC 12 V
quantity	2	Input current	0.5 A
Network		Power consumption (typical)	3.37 W
incluion k	IEEE 802.1p, IEEE 802.3, IEEE	Power over Ethernet (PoE)	
Networking standards *	802.3ab, IEEE 802.3az, IEEE	Power over Ethernet (PoE) *	×
100	802.3bz, IEEE 802.3u, IEEE 802.3x	Operational conditions	
10G support * Copper ethernet cabling technology Auto MDI/MDI-X Ethernet LAN data rates MAC address auto-learning	★ 10BASE-T, 100BASE-T, 1000BASE-T, 2500BASE-T ✓ 10,100,1000,2500 Mbit/s	Operating temperature (T-T) Storage temperature (T-T) Operating relative humidity (H-H) Storage relative humidity (H-H) Heat dissipation	0 - 40 °C -10 - 70 °C 10 - 90% 5 - 90% 14.28 BTU/h
supported	<ul> <li>Image: A second s</li></ul>	Weight & dimensions	
Data transmission Switching capacity * Forwarding rate MAC address table *	20 Gbit/s 14.88 Mpps 2000 entries	Width Depth Height Weight	145 mm 28 mm 82 mm 295.2 g
Store-and-forward	1	Sustainability	
Number of queues Packet buffer memory	8 2 MB	Sustainability compliance	1
Design		Certificates	
Product colour	Black	Compliance certificates	BSMI, CE, Low Voltage Directive (LVD), RoHS





790069470240

0790069470240

Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.