
## D-Link

## D-Link DMS-1100-10TP verkkokytkin Hallittu L2 2.5G Ethernet (100/1000/2500) Power over Ethernet -tuki 1U musta

Tuotemerkki : D-Link Tuotekoodi: DMS-1100-10TP

Tuotteen nimi: DMS-1100-10TP







Management features		Security	
Switch type *	Managed	IGMP entries	192
Switch layer	L2	Security algorithms	SNMP, SSL/TLS
Quality of Service (QoS) support	<b>✓</b>	DoS attack prevention	<b>✓</b>
System event log	✓ RFC768 UDP, RFC791 IP, RFC792 ICMP, RFC793 TCP, RFC826 ARP,	Queue scheduling algorithms	Strict Priority Queue (SPQ), Deficit weighted round robin (DWRR), Weighted Round Robin (WRR)
MIB support	RFC1213 MIB II, RFC768 UDP, RFC791 IP, RFC792 ICMP, RFC793 TCP, RFC826 ARP, RFC1213 MIB II	Multicast features	
		Multicast support	✓
Ports & interfaces		MLD entries	192
Basic switching RJ-45 Ethernet ports	0	Design	
quantity *	ŭ	Rack mounting *	✓
Basic switching RJ-45 Ethernet ports type *	2.5G Ethernet (100/1000/2500)	Form factor	10
SFP+ module slots quantity	2	Product colour	Black
Network		LED indicators	Activity, Fan fail, Link, PoE, Power, Speed
Networking standards *	IEEE 802.1D, IEEE 802.1Q, IEEE 802.1w, IEEE 802.3ab, IEEE 802.3ad, IEEE 802.3ae, IEEE 802.3af, IEEE 802.3at, IEEE 802.3az, IEEE 802.3bz, IEEE 802.3u, IEEE 802.3x, IEEE 802.3z	Number of fans Safety	1 fan(s) cUL, CB, CE, CCC, BSMI
		Performance	
		Maximum cable length	100 m
10G support *	✓	Mean time between failures (MTBF)	676329 h
Copper ethernet cabling technology	100BASE-TX, 1000BASE-T	Power	
Cable types supported	Cat5e	AC input voltage	100 - 240 V
Port mirroring	✓	Power consumption (max)	293.4 W
Flow control support	✓	Power over Ethernet (PoE)	
Link aggregation	✓	Power over Ethernet (PoE) *	✓
Auto MDI/MDI-X	✓	Power over Ethernet plus (PoE+)	8
Spanning tree protocol	✓	ports quantity	
Head-of-line (HOL) blocking	✓	Total Power over Ethernet (PoE) budget	240 W
Ethernet Ring Protection Switching (ERPS)	✓	Operational conditions	
VLAN support	1	Operating temperature (T-T)	-5 - 50 °C
Virtual LAN features	Voice VLAN, Tagged VLAN, Portbased VLAN	Storage temperature (T-T) Operating relative humidity (H-H)	-40 - 70 °C 0 - 95%
Number of VLANs	4094	Storage relative humidity (H-H)	0 - 95%

Optical fiber		Weight & dimensions	
Fiber ethernet cabling technology	1000BASE-X	Width	440 mm
Data transmission		Depth	250 mm
Switching capacity * Throughput	80 Gbit/s 59.52 Mpps 16000 entries ✓	Height Weight	44 mm 3.43 kg
MAC address table *		Certificates	
Store-and-forward		Certification	CE, FCC, C-Tick, VCCI, BSMI, CCC
Jumbo frames support	✓	Logistics data	
Jumbo frames	9216	Harmonized System (HS) code	85176990
Security			
DHCP features	DHCP client		
IGMP snooping	<b>✓</b>		





790069437168

0790069437168

Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.