



DELL UltraSharp U4924DW LED display 124,5 cm (49") 5120 x 1440 pikseliä 5K Ultra HD LCD musta, Hopea

Tuotemerkki : DELL

Tuoteperhe: UltraSharp

Tuotekoodi: DELL-U4924DW

Tuotteen nimi : U4924DW

DELL UltraSharp U4924DW. Näytön halkaisija: 124,5 cm (49"), Näytön erottelutarkkuus: 5120 x 1440 pikseliä, HD-tyyppi: 5K Ultra HD, Näytön teknologia: LCD, Vasteaika (tyypillinen): 14 ms, Vakiokuvasuhde: 32:9, Katselukulma, vaakasuora: 178°, Katselukulma, pystysuora: 178°. Sisäiset kaiuttimet. Sisäänrakennettu USB-keskus, USB-keskuksen versio: 3.2 Gen 2 (3.1 Gen 2). VESA-kiinnitys, Korkeudensäätö. Tuotteen väri: musta, Hopea



Display		Ergonomics	
Display diagonal *	124.5 cm (49")	Cable lock slot *	✓
Display resolution *	5120 x 1440 pixels	Cable lock slot type	Kensington
HD type *	5K Ultra HD	Height adjustment *	✓
Native aspect ratio *	32:9	Height adjustment	12 cm
Display technology *	LCD	Pivot	✗
Panel type *	IPS	Swivelling	✓
Backlight type	LED	Swivel angle range	-170 - 170°
Touchscreen *	✗	Tilt adjustment	✓
Display brightness (typical)	350 cd/m ²	Tilt angle range	-5 - 21°
Response time *	14 ms	Picture-in-Picture	✓
Anti-glare screen	✓	On Screen Display (OSD)	✓
Screen shape *	Curved	Plug and Play	✓
Screen curvature rating	3800R	LED indicators	✓
Supported graphics resolutions	640 x 400, 640 x 480 (VGA), 720 x 400, 800 x 600 (SVGA), 1024 x 768 (XGA), 1152 x 864 (XGA+), 1280 x 1024 (SXGA), 1600 x 900, 1920 x 1080 (HD 1080), 2560 x 1080, 2560 x 1440, 3840 x 1080, 5120 x 1440	Power	
		Energy efficiency class (SDR) *	G
Supported video modes	480p, 576p, 720p, 1080i, 1080p	Energy efficiency class (HDR) *	Not available
Contrast ratio (typical) *	2000:1	Energy consumption (SDR) per 1000 hours *	45 kWh
Maximum refresh rate *	60 Hz	Power consumption (typical) *	45 W
Viewing angle, horizontal	178°	Power consumption (standby) *	0.3 W
Viewing angle, vertical	178°	Power consumption (max)	290 W
Display number of colours *	1.07 billion colours	Power consumption (off)	0.3 W
Response time (fast)	5 ms	AC input voltage	100 - 240 V
Pixel pitch	0.234 x 0.234 mm	AC input frequency	50 - 60 Hz
Pixel density	109 ppi	Input current	3.6 A
Horizontal scan range	25 - 115 kHz	Power supply type	Internal
Vertical scan range	24 - 86 Hz	Energy efficiency scale	A to G

Display		Power			
Viewable size, horizontal	119.8 cm	European Product Registry for Energy Labelling (EPREL) code	1367150		
Viewable size, vertical	33.7 cm	Operational conditions			
Viewable size diagonal	124.5 cm				
Display diagonal (metric)	124.46 cm				
High Dynamic Range (HDR) supported	✗				
Surface hardness	3H				
Colour depth	10 bit	Operating temperature (T-T)	0 - 40 °C		
Colour gamut standard	DCI-P3	Storage temperature (T-T)	-20 - 60 °C		
Colour gamut	98%	Operating relative humidity (H-H)	10 - 80%		
sRGB coverage (typical)	100%	Storage relative humidity (H-H)	5 - 90%		
Performance		Operating altitude	0 - 5000 m		
		Non-operating altitude	5000 - 12192 m		
		Weight & dimensions			
		Width (with stand)	1214.9 mm		
		Depth (with stand)	269.1 mm		
NVIDIA G-SYNC *	✗	Height (with stand)	520.6 mm		
AMD FreeSync *	✗	Weight (with stand)	15.8 kg		
Flicker-free technology	✓	Width (without stand)	1214.9 mm		
Low Blue Light technology	✓	Depth (without stand)	112.1 mm		
Multimedia		Height (without stand)	365.9 mm		
		Weight (without stand)	12.2 kg		
		Bezel width (side)	1.1 cm		
		Bezel width (top)	1.21 cm		
		Bezel width (bottom)	1.69 cm		
Design		Packaging data			
		Package weight	27.7 kg		
Market positioning *	Office	Packaging content			
Product colour *	Black, Silver				
Front bezel colour	Black				
Detachable stand	✓				
Feet colour	Silver				
Ports & interfaces		Sustainability			
				Sustainability certificates	ENERGY STAR, TCO
				Doesn't contain	PVC/BFR
				Carbon footprint	
				Total carbon footprint (kg of CO2e)	1140
		Total carbon emissions, standard deviation (kg of CO2e)	318		
		Carbon emissions, manufacturing (kg of CO2e)	536		
		Carbon emissions, logistics (kg of CO2e)	136		
		Carbon emissions, energy usage (kg of CO2e)	455		
		Carbon emissions, end-of-life (kg of CO2e)	16		
		Total carbon emissions, w/o use phase (kg of CO2e)	688		
		PAIA version	1.3.1, 2022		
		Other features			
		Heavy metals free	Hg (mercury)		
		Compliance certificates	RoHS		
		Ethernet LAN (RJ-45) ports	1		
		Network			
		Wi-Fi	✗		
		Ergonomics			
		VESA mounting *	✓		
Panel mounting interface	100 x 100,200 x 100 mm				



0884116442394



884116442394



5397184657133

Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.